

STATE OF OKLAHOMA
DEPARTMENT OF HIGHWAYS
PLANS AND SURVEY DEPARTMENT

FLOOD INFORMATION FORM

To be used in obtaining and transmitting flood water elevations for Plans & Survey office record files. This information to be obtained by all Chiefs of Party in their vicinity in times of unusual high water, or at any time available from a reliable source. The elevations can be recorded by level reading, by measurement from bridge floor, in relation to a house, above roadbed or any other dependable, clear manner that fits the situation, the highest order possible to be used. Separate report to be made on each crossing or place obtained.

County Cherokee Date highwater occurred August 15, 1948

Highway number SH 10 Name of stream Illinois River

Direction and distance from nearest town, village or store 3.0 miles east of Tahlequah, 500' north of the Jct of SH 10, US 62 and SH 51 at Wood Bridge over SH 10

Section, Township and Range Section 26 T17N R22E

Description of Location _____

Method obtained Wye level - 2.5' below floor of Wood Bridge

Elevation _____ Source of levels _____

Was highwater mark obtained from actual water, drift, local resident, U. S. Engineers, etc? A. W. Foreman, Maintenance Supt, State Highway Dept. Box 220, Tahlequah, Oklahoma


Explanatory Remarks This highwater is the highest in 15 years with the exception of the time that the dam broke on Lake Francis in 1943

Location to be shown on back of this sheet as a check.

Field Note: To be sent to Engr. of Plans & Survey (1 copy).
Office Note: To be filed in Flood Information by Counties.

W. N. McLaughlin
Chief of Party
Aug. 17, 1948
Date

LOO NO. 2



Plans & Survey Dept.
Form No. 16
Rev. July 10, 1947

STATE OF OKLAHOMA
DEPARTMENT OF HIGHWAYS
PLANS AND SURVEY DEPARTMENT

FLOOD INFORMATION FORM

To be used in obtaining and transmitting flood water elevations for Plans & Survey office record files. This information to be obtained by all Chiefs of Party in their vicinity in times of unusual high water, or at any time available from a reliable source. The elevations can be recorded by level reading, by measurement from bridge floor, in relation to a house, above roadbed or any other dependable, clear manner that fits the situation, the highest order possible to be used. Separate report to be made on each crossing or place obtained.

County CHEROKEE Date highwater occurred August 15, 1948

Highway number S.H. 10 Name of stream Illinois River

Direction and distance from nearest town, village or store 3 Miles East of Tahlequah, 500' North of the Jet of S.H. 10, U.S. 62 & S.H. 51 At Wood Bridge over S.H. 10

Section, Township and Range Section 26 T. 17-N R. 22-E

Description of Location _____

Method obtained WYE LEVEL - 2.5 Feet Below Floor of Wood Bridge

Elevation _____ Source of levels _____

Was highwater mark obtained from actual water, drift, local resident, U. S. Engineers, etc? A.W. Foreman - Maintenance Supt, State Hwy Dept Box 220 Tahlequah, Okla


Explanatory Remarks This highwater is the highest in 15 years with the exception of the time that the Dam Broke on Lake Francis in 1943

Location to be shown on back of this sheet as a check.

Field Note: To be sent to Engr. of Plans & Survey (1 copy).
Office Note: To be filed in Flood Information by Counties.

W.N. McLaughlin
Chief of Party

Aug 17, 1948
Date



R-22-E

R-23-E

T-18-N

T-17-N

