

STATE OF OKLAHOMA
DEPARTMENT OF HIGHWAYS
PLANS AND SURVEY DEPARTMENT

FLOOD INFORMATION FORM

To be used in obtaining and transmitting flood water elevations for Plans & Survey office record files. This information to be obtained by all Chiefs of Party in their vicinity in times of unusual high water, or at any time available from a reliable source. The elevations can be recorded by level reading, by measurement from bridge floor, in relation to a house, above roadbed or any other dependable, clear manner that fits the situation, the highest order possible to be used. Separate report to be made on each crossing or place obtained.

County COTTON Date highwater occurred May-18-19, 1951

Highway number S.H. 53 Name of stream EAST CACHE CR

Direction and distance from nearest town, village or store 2.1 MILES
EAST OF WALTERS

Section, Township and Range Between Sec 20E 29-T 23 R 10W

Description of Location At the East Relief Overflow Structure, a stake
Set at Max H.W. Stage by Maint. Foreman (Neally)

Method obtained _____

HW. is 13 Lower than the Bridge Floor.
Elevation at East Relief Structure Source of levels _____

Was highwater mark obtained from actual water, drift, local resident, U. S. Engineers, etc? Obtained from a mark shown

to me by State Highway Maint. Foreman "Neally"

Explanatory Remarks Mr. Neally was there when this (Max mark)
was reached - This was obtained by the use
of a wye level - by A. B. Stephens and Roy Flowers

Location to be shown on back of this sheet as a check.

Field Note: To be sent to Engr. of Plans & Survey (1 copy).
Office Note: To be filed in Flood Information by Counties.

A. B. Stephens
RES ENGINEER
May 23, 1951
Date

NOTE: SEE NO. 1 ATTACHED MAP FOR LOCATION.

LOC. # 1