

OFFICE OF THE DELAWARE RIVER MASTER, MILFORD, PA.

Web address: <http://water.usgs.gov/orh/nrwww/odrm>

Summary river data for January 1 - 7, 2007 (preliminary data-subject to revision)

RESERVOIR OPERATION DATA

Millions of gallons - 24 hour period, local time

Date	Discharge to river			Diversions to New York City water supply			
	Pepacton	Cannonsville	Neversink	Pepacton	Cannonsville	Neversink	Average June 1, 2006 to date
	release begin 1200	release end 2400	release begin 1500	beginning 0800	beginning 0800	beginning 0800	
Jan. 1	120	539	62	448	0	0	436
2	120	651	122	329	0	74	436
3	120	649	123	303	0	108	436
4	120	650	123	303	0	102	436
5	120	608	123	301	0	109	436
6	120	607	123	302	0	0	435
7	126	649	119	301	0	0	434

Pepacton Reservoir (P):	Available storage Jan. 8, 2007 (0800) Spillway crest elevation 1,280.00 ft.	133.419 billion gals. 95.2 % (elev. 1,276.28 ft.) 140.190 billion gallons.
Cannonsville Reservoir (C):	Available storage Jan. 8, 2007 (0800) Spillway crest elevation 1,150.00 ft.	92.299 billion gals. 96.4 % (elev. 1,147.76 ft.) 95.706 billion gallons.
Neversink Reservoir (N):	Available storage Jan. 8, 2007 (0800) Spillway crest elevation 1,440.00 ft.	34.306 billion gals. 98.2 % (elev. 1,438.71 ft.) 34.941 billion gallons.
Combined contents, PCN:	Available storage Jan. 8, 2007 (0800) Combined capacity at spillway level.	260.024 billion gals. 96.0 % 270.837 billion gallons.
Lake Wallenpaupack:	Available storage Jan. 7, 2007 (2400) Spillway crest elevation 1,190.00 ft.	22.482 billion gals. 63.4 % (elev. 1,183.0 ft.) 35.451 billion gallons.

SEGREGATION OF FLOW, DELAWARE RIVER AT MONTAGUE AND
PRECIPITATION IN UPPER DELAWARE RIVER BASIN

Discharge in cubic feet per second, local time as routed to Montague

Date	Releases from N.Y.C. Reservoirs				Power releases		Computed uncon- trolled ²	Total Discharge	Precipitation (inches)	
	Directed release ¹	Pepacton	Cannons- ville	Never- sink	Wallen- paupack	Rio Reservoir			Daily	Cumul.
Jan. 1	0	186	529	85	305	163	3,962	5,230	.44	.44
2	0	186	432	85	238	291	6,008	7,240	.04	.48
3	0	186	834	96	282	181	5,381	6,960	0	.48
4	0	186	1,007	189	291	96	4,511	6,280	0	.48
5	0	186	1,004	190	298	78	4,284	6,040	0	.48
6	0	186	1,006	190	454	46	6,288	8,170	.90	1.38
7	0	186	941	190	582	177	12,924	15,000	.05	1.43

1. Release directed to maintain a flow at Montague of 1,750 cfs.

2. Includes conservation release of 60 cfs from Rio Reservoir.

Diversions by New Jersey through the Delaware and Raritan Canal January 1 - 7, 2007, averaged 83.0 mgd. The average diversion and maximum diversion for the 30-day period ending January 7, 2007, are currently unavailable.

OFFICE OF THE DELAWARE RIVER MASTER, MILFORD, PA.

Web address: <http://water.usgs.gov/orh/nrwww/odrm>

Summary river data for January 8 - 14, 2007 (preliminary data-subject to revision)

RESERVOIR OPERATION DATA

Millions of gallons - 24 hour period, local time

Date	Discharge to river				Diversions to New York City water supply			
	Pepacton	Cannonsville		Neversink	Pepacton	Cannonsville	Neversink	Average
	release begin 1200	release end 2400	spill begin 0800	release begin 1500	beginning 0800	beginning 0800	beginning 0800	June 1, 2006 to date
Jan. 8	356	650	0	38	2	0	321	434
9	453	652	0	123	0	0	326	433
10	451	648	0	123	0	0	349	433
11	452	645	0	123	196	0	347	434
12	452	647	0	123	70	0	346	433
13	452	648	8	123	0	0	346	433
14	452	649	86	122	0	0	345	433

Pepacton Reservoir (P):	Available storage Jan. 15, 2007 (0800)	138.223 billion gals.	98.6 % (elev. 1,278.93 ft.)
	Spillway crest elevation 1,280.00 ft.	140.190 billion gallons.	
Cannonsville Reservoir (C):	Available storage Jan. 15, 2007 (0800)	96.543 billion gals.	100.9 % (elev. 1,150.52 ft.)
	Spillway crest elevation 1,150.00 ft.	95.706 billion gallons.	
Neversink Reservoir (N):	Available storage Jan. 15, 2007 (0800)	34.028 billion gals.	97.4 % (elev. 1,438.14 ft.)
	Spillway crest elevation 1,440.00 ft.	34.941 billion gallons.	
Combined contents, PCN:	Available storage Jan. 15, 2007 (0800)	268.794 billion gals.	99.2 %
	Combined capacity at spillway level.	270.837 billion gallons.	
Lake Wallenpaupack:	Available storage Jan. 14, 2007 (2400)	22.124 billion gals.	62.4 % (elev. 1,182.8 ft.)
	Spillway crest elevation 1,190.00 ft.	35.451 billion gallons.	

SEGREGATION OF FLOW, DELAWARE RIVER AT MONTAGUE AND
PRECIPITATION IN UPPER DELAWARE RIVER BASIN

Discharge in cubic feet per second, local time as routed to Montague

Date	Releases from N.Y.C. Reservoirs				Power releases		Computed uncon- trolled ²	Total Discharge	Precipitation	
	Directed release ¹	Pepacton	Cannons- ville	Never- sink	Wallen- paupack	Rio Reservoir			(inches)	
							Daily	Cumul.		
Jan. 8	0	186	939	190	513	305	13,767	15,900	.70	2.13
9	0	186	1,004	184	785	727	18,314	21,200	.17	2.30
10	0	195	1,006	59	832	709	13,199	16,000	0	2.30
11	0	551	1,009	190	832	699	9,619	12,900	0	2.30
12	0	701	1,002	190	832	340	7,635	10,700	0	2.30
13	0	698	998	190	832	660	6,722	10,100	.13	2.43
14	0	699	1,001	190	832	383	7,095	10,200	.17	2.60

1. Release directed to maintain a flow at Montague of 1,750 cfs.

2. Includes conservation release of 60 cfs from Rio Reservoir.

Diversions by New Jersey through the Delaware and Raritan Canal January 8 - 14, 2007, averaged 86.6 mgd. The average diversion and maximum diversion for the 30-day period ending January 14, 2007 are currently unavailable.

OFFICE OF THE DELAWARE RIVER MASTER, MILFORD, PA.

Web address: <http://water.usgs.gov/orh/nrwww/odrm>

Summary river data for January 15 - 21, 2007 (preliminary data-subject to revision)

RESERVOIR OPERATION DATA

Millions of gallons - 24 hour period, local time

Date	Discharge to river					Diversions to New York City water supply			
	Pepacton		Cannonsville		Neversink	Pepacton	Cannonsville	Neversink	Average June 1, 2006 to date
	release begin 1200	spill begin 0800	release end 2400	spill begin 0800	release begin 1500	beginning 0800	beginning 0800	beginning 0800	
Jan. 15	452	0	649	422	123	0	0	345	432
16	452	13	648	886	123	0	0	345	432
17	452	162	645	982	123	2	0	345	432
18	452	321	646	879	123	0	0	345	431
19	452	318	645	638	123	166	0	226	431
20	452	194	645	575	122	205	0	194	431
21	452	88	645	430	123	204	0	193	431

Pepacton Reservoir (P):	Available storage Jan. 22, 2007 (0800)	140.394 billion gals. 100.1 % (elev. 1,280.11 ft.)
	Spillway crest elevation 1,280.00 ft.	140.190 billion gallons.
Cannonsville Reservoir (C):	Available storage Jan. 22, 2007 (0800)	97.106 billion gals. 101.5 % (elev. 1,150.87 ft.)
	Spillway crest elevation 1,150.00 ft.	95.706 billion gallons.
Neversink Reservoir (N):	Available storage Jan. 22, 2007 (0800)	33.379 billion gals. 95.5 % (elev. 1,436.80 ft.)
	Spillway crest elevation 1,440.00 ft.	34.941 billion gallons.
Combined contents, PCN:	Available storage Jan. 22, 2007 (0800)	270.879 billion gals. 100.0 %
	Combined capacity at spillway level.	270.837 billion gallons.
Lake Wallenpaupack:	Available storage Jan. 21, 2007 (2400)	21.407 billion gals. 60.4 % (elev. 1,182.4 ft.)
	Spillway crest elevation 1,190.00 ft.	35.451 billion gallons.

SEGREGATION OF FLOW, DELAWARE RIVER AT MONTAGUE AND
PRECIPITATION IN UPPER DELAWARE RIVER BASIN

Discharge in cubic feet per second, local time as routed to Montague

Date	Releases from N.Y.C. Reservoirs				Power releases		Computed uncon- trolled ²	Total Discharge	Precipitation	
	Directed release ¹	Pepacton	Cannons- ville	Never- sink	Wallen- paupack	Rio Reservoir			(inches)	
							Daily	Cumul.		
Jan. 15	0	699	1,002	190	832	390	8,587	11,700	.42	3.02
16	0	699	1,004	189	832	624	14,852	18,200	.31	3.33
17	0	699	1,004	190	832	507	13,368	16,600	0	3.33
18	0	699	1,002	190	832	514	10,363	13,600	0	3.33
19	0	699	998	190	738	305	9,270	12,200	.03	3.36
20	0	699	999	190	512	238	8,462	11,100	.01	3.37
21	0	699	998	190	516	238	6,919	9,560	0	3.37

1. Release directed to maintain a flow at Montague of 1,750 cfs.

2. Includes conservation release of 60 cfs from Rio Reservoir.

Diversions by New Jersey through the Delaware and Raritan Canal January 15 - 21, 2007, averaged 96.7 mgd. The average diversion for the 30-day period ending January 21, 2007 was 87.2 mgd and the maximum diversion was 98 mg on January 7, 14, and 16, 2007.

OFFICE OF THE DELAWARE RIVER MASTER, MILFORD, PA.

Web address: <http://water.usgs.gov/orh/nrwww/odrm>

Summary river data for January 22 - 28, 2007 (preliminary data-subject to revision)

RESERVOIR OPERATION DATA

Millions of gallons - 24 hour period, local time

Date	Discharge to river					Diversions to New York City water supply			
	Pepacton		Cannonsville		Neversink	Pepacton	Cannonsville	Neversink	Average June 1, 2006 to date
	release begin 1200	spill begin 0800	release end 2400	spill begin 0800	release begin 1500	beginning 0800	beginning 0800	beginning 0800	
Jan. 22	452	31	644	314	123	213	0	229	431
23	452	2	644	216	123	372	76	59	431
24	452	0	645	120	118	399	122	49	432
25	452	0	648	40	87	364	99	91	432
26	451	0	649	1	58	353	100	100	433
27	452	0	649	0	55	308	0	100	433
28	452	0	648	0	55	353	197	102	433

Pepacton Reservoir (P):	Available storage Jan. 29, 2007 (0800)	139.693 billion gals.	98.2 % (elev. 1,278.64 ft.)
	Spillway crest elevation 1,280.00 ft.	140.190 billion gallons.	
Cannonsville Reservoir (C):	Available storage Jan. 29, 2007 (0800)	94.793 billion gals.	99.0 % (elev. 1,149.40 ft.)
	Spillway crest elevation 1,150.00 ft.	95.706 billion gallons.	
Neversink Reservoir (N):	Available storage Jan. 29, 2007 (0800)	33.000 billion gals.	94.4 % (elev. 1,436.01 ft.)
	Spillway crest elevation 1,440.00 ft.	34.941 billion gallons.	
Combined contents, PCN:	Available storage Jan. 29, 2007 (0800)	265.486 billion gals.	98.0 %
	Combined capacity at spillway level.	270.837 billion gallons.	
Lake Wallenpaupack:	Available storage Jan. 28, 2007 (2400)	21.407 billion gals.	60.4 % (elev. 1,182.4 ft.)
	Spillway crest elevation 1,190.00 ft.	35.451 billion gallons.	

SEGREGATION OF FLOW, DELAWARE RIVER AT MONTAGUE AND
PRECIPITATION IN UPPER DELAWARE RIVER BASIN

Discharge in cubic feet per second, local time as routed to Montague

Date	Releases from N.Y.C. Reservoirs				Power releases		Computed uncon- trolled ²	Total Discharge	Precipitation	
	Directed release ¹	Pepacton	Cannons- ville	Never- sink	Wallen- paupack	Rio Reservoir			(inches)	
							Daily	Cumul.		
Jan. 22	0	699	998	189	408	177	5,899	8,370	0	3.37
23	0	699	998	190	314	177	5,322	7,700	0	3.37
24	0	699	996	190	346	209	4,640	7,080	0	3.37
25	0	699	996	190	240	152	4,243	6,520	.01	3.38
26	0	699	998	183	711	202	3,497	6,290	0	3.38
27	0	699	1,002	135	357	174	2,893	5,260	0	3.38
28	0	699	1,004	90	0	0	3,027	4,820	.01	3.39

1. Release directed to maintain a flow at Montague of 1,750 cfs.

2. Includes conservation release of 60 cfs from Rio Reservoir.

Diversions by New Jersey through the Delaware and Raritan Canal January 22 - 28, 2007, averaged 93.0 mgd. The average diversion for the 30-day period ending January 28, 2007 was 90.0 mgd and the maximum diversion was 98 mg on January 7, 14, and 16, 2007.

OFFICE OF THE DELAWARE RIVER MASTER, MILFORD, PA.

Web address: <http://water.usgs.gov/orh/nrwww/odrm>

Summary river data for January 29 - February 4, 2007 (preliminary data-subject to revision)

RESERVOIR OPERATION DATA

Millions of gallons - 24 hour period, local time

Date	Discharge to river			Diversions to New York City water supply			
	Pepacton	Cannonsville	Neversink	Pepacton	Cannonsville	Neversink	Average June 1, 2006 to date
	release begin 1200	release end 2400	release begin 1500	beginning 0800	beginning 0800	beginning 0800	
Jan. 29	452	649	55	351	142	104	434
30	452	646	55	349	134	106	435
31	452	647	55	329	146	3	435
Feb. 1	452	645	55	436	137	152	436
2	452	645	55	463	125	148	437
3	452	644	55	464	0	0	437
4	445	643	55	466	13	1	438

Pepacton Reservoir (P):	Available storage Feb. 5, 2007 (0800)	133.329 billion gals.	95.1 % (elev. 1,276.23 ft.)
	Spillway crest elevation 1,280.00 ft.	140.190 billion gallons.	
Cannonsville Reservoir (C):	Available storage Feb. 5, 2007 (0800)	91.492 billion gals.	95.6 % (elev. 1,147.23 ft.)
	Spillway crest elevation 1,150.00 ft.	95.706 billion gallons.	
Neversink Reservoir (N):	Available storage Feb. 5, 2007 (0800)	32.671 billion gals.	93.5 % (elev. 1,435.32 ft.)
	Spillway crest elevation 1,440.00 ft.	34.941 billion gallons.	
Combined contents, PCN:	Available storage Feb. 5, 2007 (0800)	257.492 billion gals.	95.1 %
	Combined capacity at spillway level.	270.837 billion gallons.	
Lake Wallenpaupack:	Available storage Feb. 4, 2007 (2400)	21.228 billion gals.	59.9 % (elev. 1,182.3 ft.)
	Spillway crest elevation 1,190.00 ft.	35.451 billion gallons.	

SEGREGATION OF FLOW, DELAWARE RIVER AT MONTAGUE AND
PRECIPITATION IN UPPER DELAWARE RIVER BASIN

Discharge in cubic feet per second, local time as routed to Montague

Date	Releases from N.Y.C. Reservoirs				Power releases		Computed uncon- trolled ²	Total Discharge	Precipitation	
	Directed release ¹	Pepacton	Cannons- ville	Never- sink	Wallen- paupack	Rio Reservoir			(inches)	
							Daily	Cumul.		
Jan. 29	0	698	1,004	85	98	0	3,325	5,210	0	3.39
30	0	699	1,002	85	300	0	3,044	5,130	0	3.39
31	0	699	1,004	85	361	177	2,844	5,170	.01	3.40
Feb. 1	0	699	999	85	249	181	2,787	5,000	0	0
2	0	699	1,001	85	250	191	2,534	4,760	.01	.01
3	0	699	998	85	452	167	2,299	4,700	.12	.13
4	0	699	998	85	0	0	2,698	4,480	0	.13

1. Release directed to maintain a flow at Montague of 1,750 cfs.

2. Includes conservation release of 60 cfs from Rio Reservoir.

Diversions by New Jersey through the Delaware and Raritan Canal January 29 - February 4, 2007, averaged 90.6 mgd. The average diversion for the 30-day period ending February 4, 2007 was 92.1 mgd and the maximum daily diversion was 98 mg on January 7, 14, and 16, 2007.

OFFICE OF THE DELAWARE RIVER MASTER, MILFORD, PA.

Web address: <http://water.usgs.gov/orh/nrwww/odrm>

Summary river data for February 5 -11, 2007 (preliminary data-subject to revision)

RESERVOIR OPERATION DATA

Millions of gallons - 24 hour period, local time

Date	Discharge to river			Diversions to New York City water supply			
	Pepacton	Cannonsville	Neversink	Pepacton	Cannonsville	Neversink	Average June 1, 2006 to date
	release begin 1200	release end 2400	release begin 1500	beginning 0800	beginning 0800	beginning 0800	
Feb. 5	421	595	55	466	143	155	439
6	418	581	55	462	143	157	440
7	441	648	55	451	141	74	441
8	348	598	55	458	143	98	442
9	248	436	55	458	127	123	443
10	160	290	55	459	0	0	443
11	120	177	55	457	2	0	443

Pepacton Reservoir (P):	Available storage Feb. 12, 2007 (0800)	128.972 billion gals.	92.0 % (elev. 1,273.78 ft.)
	Spillway crest elevation 1,280.00 ft.	140.190 billion gallons.	
Cannonsville Reservoir (C):	Available storage Feb. 12, 2007 (0800)	88.845 billion gals.	92.8 % (elev. 1,145.49 ft.)
	Spillway crest elevation 1,150.00 ft.	95.706 billion gallons.	
Neversink Reservoir (N):	Available storage Feb. 12, 2007 (0800)	32.103 billion gals.	91.9 % (elev. 1,434.12 ft.)
	Spillway crest elevation 1,440.00 ft.	34.941 billion gallons.	
Combined contents, PCN:	Available storage Feb. 12, 2007 (0800)	249.920 billion gals.	92.3 %
	Combined capacity at spillway level.	270.837 billion gallons.	
Lake Wallenpaupack:	Available storage Feb. 11, 2007 (2400)	20.690 billion gals.	58.4 % (elev. 1,182.0 ft.)
	Spillway crest elevation 1,190.00 ft.	35.451 billion gallons.	

SEGREGATION OF FLOW, DELAWARE RIVER AT MONTAGUE AND
PRECIPITATION IN UPPER DELAWARE RIVER BASIN

Discharge in cubic feet per second, local time as routed to Montague

Date	Releases from N.Y.C. Reservoirs				Power releases		Computed uncon- trolled ²	Total Discharge	Precipitation	
	Directed release ¹	Pepacton	Cannons- ville	Never- sink	Wallen- paupack	Rio Reservoir			(inches)	
							Daily	Cumul.		
Feb. 5	0	699	996	85	36	0	1,584	3,400	0	.13
6	0	699	995	85	382	0	1,339	3,500	0	.13
7	0	688	920	85	257	0	1,450	3,400	0	.13
8	0	651	899	85	378	0	1,587	3,600	0	.13
9	0	647	1,002	85	446	0	1,920	4,100	0	.13
10	0	682	925	85	258	0	1,850	3,800	0	.13
11	0	538	674	85	0	0	1,503	2,800	0	.13

1. Release directed to maintain a flow at Montague of 1,750 cfs.

2. Includes conservation release of 60 cfs from Rio Reservoir.

Diversions by New Jersey through the Delaware and Raritan Canal February 5 - 11, 2007, averaged 95.0 mgd. The average diversion for the 30-day period ending February 11, 2007 was 94.0 mgd and the maximum daily diversion was 99 mg on February 7, 9, and 10, 2007.

OFFICE OF THE DELAWARE RIVER MASTER, MILFORD, PA.

Web address: <http://water.usgs.gov/orh/nrwww/odrm>

Summary river data for February 12 -18, 2007 (preliminary data-subject to revision)

RESERVOIR OPERATION DATA

Millions of gallons - 24 hour period, local time

Date	Discharge to river			Diversions to New York City water supply			
	Pepacton	Cannonsville	Neversink	Pepacton	Cannonsville	Neversink	Average June 1, 2006 to date
	release begin 1200	release end 2400	release begin 1500	beginning 0800	beginning 0800	beginning 0800	
Feb. 12	120	161	55	457	141	124	444
13	120	161	55	458	137	221	446
14	120	164	55	458	137	228	447
15	127	164	55	368	135	193	448
16	200	271	55	353	134	75	449
17	145	648	55	352	0	0	448
18	176	650	55	351	11	0	448

Pepacton Reservoir (P):	Available storage Feb. 19, 2007 (0800)	126.412 billion gals.	90.2 % (elev. 1,272.32 ft.)
	Spillway crest elevation 1,280.00 ft.	140.190 billion gallons.	
Cannonsville Reservoir (C):	Available storage Feb. 19, 2007 (0800)	87.161 billion gals.	91.1 % (elev. 1,144.35 ft.)
	Spillway crest elevation 1,150.00 ft.	95.706 billion gallons.	
Neversink Reservoir (N):	Available storage Feb. 19, 2007 (0800)	31.332 billion gals.	89.7 % (elev. 1,432.47 ft.)
	Spillway crest elevation 1,440.00 ft.	34.941 billion gallons.	
Combined contents, PCN:	Available storage Feb. 19, 2007 (0800)	244.905 billion gals.	90.4 %
	Combined capacity at spillway level.	270.837 billion gallons.	
Lake Wallenpaupack:	Available storage Feb. 18, 2007 (2400)	20.511 billion gals.	57.9 % (elev. 1,181.9 ft.)
	Spillway crest elevation 1,190.00 ft.	35.451 billion gallons.	

SEGREGATION OF FLOW, DELAWARE RIVER AT MONTAGUE AND
PRECIPITATION IN UPPER DELAWARE RIVER BASIN

Discharge in cubic feet per second, local time as routed to Montague

Date	Releases from N.Y.C. Reservoirs				Power releases		Computed uncon- trolled ²	Total Discharge	Precipitation	
	Directed release ¹	Pepacton	Cannons- ville	Never- sink	Wallen- paupack	Rio Reservoir			(inches)	
							Daily	Cumul.		
Feb. 12	0	384	449	85	36	0	1,646	2,600	0	.13
13	0	248	274	85	356	0	1,637	2,600	0	.13
14	0	186	249	85	445	0	1,635	2,600	1.07	1.20
15	0	186	249	85	484	0	1,596	2,600	1.30	2.50
16	0	186	254	85	427	0	1,548	2,500	0	2.50
17	0	186	254	85	338	0	1,537	2,400	0	2.50
18	0	196	419	85	0	0	1,600	2,300	0	2.50

1. Release directed to maintain a flow at Montague of 1,750 cfs.

2. Includes conservation release of 60 cfs from Rio Reservoir.

Diversions by New Jersey through the Delaware and Raritan Canal February 12 - 18, 2007, averaged 98.9 mgd. The average diversion for the 30-day period ending February 18, 2007 was 94.7 mgd and the maximum daily diversion was 103 mg on February 15, 2007.

OFFICE OF THE DELAWARE RIVER MASTER, MILFORD, PA.

Web address: <http://water.usgs.gov/orh/nrwww/odrm>

Summary river data for February 19 -25, 2007 (preliminary data-subject to revision)

RESERVOIR OPERATION DATA

Millions of gallons - 24 hour period, local time

Date	Discharge to river			Diversions to New York City water supply			
	Pepacton	Cannonsville	Neversink	Pepacton	Cannonsville	Neversink	Average June 1, 2006 to date
	release begin 1200	release end 2400	release begin 1500	beginning 0800	beginning 0800	beginning 0800	
Feb. 19	120	650	55	350	154	0	448
20	120	648	55	349	200	104	449
21	120	647	55	3	266	108	449
22	120	644	55	305	298	108	450
23	120	645	55	352	298	109	451
24	120	647	55	348	294	0	452
25	120	645	55	351	298	0	452

Pepacton Reservoir (P):	Available storage Feb. 26, 2007 (0800)	124.430 billion gals.	88.8 % (elev. 1,271.18 ft.)
	Spillway crest elevation 1,280.00 ft.	140.190 billion gallons.	
Cannonsville Reservoir (C):	Available storage Feb. 26, 2007 (0800)	81.958 billion gals.	85.6 % (elev. 1,140.75 ft.)
	Spillway crest elevation 1,150.00 ft.	95.706 billion gallons.	
Neversink Reservoir (N):	Available storage Feb. 26, 2007 (0800)	30.845 billion gals.	88.3 % (elev. 1,431.42 ft.)
	Spillway crest elevation 1,440.00 ft.	34.941 billion gallons.	
Combined contents, PCN:	Available storage Feb. 26, 2007 (0800)	237.233 billion gals.	87.6 %
	Combined capacity at spillway level.	270.837 billion gallons.	
Lake Wallenpaupack:	Available storage Feb. 25, 2007 (2400)	19.794 billion gals.	55.8 % (elev. 1,181.5 ft.)
	Spillway crest elevation 1,190.00 ft.	35.451 billion gallons.	

SEGREGATION OF FLOW, DELAWARE RIVER AT MONTAGUE AND
PRECIPITATION IN UPPER DELAWARE RIVER BASIN

Discharge in cubic feet per second, local time as routed to Montague

Date	Releases from N.Y.C. Reservoirs				Power releases		Computed uncon- trolled ²	Total Discharge	Precipitation	
	Directed release ¹	Pepacton	Cannons- ville	Never- sink	Wallen- paupack	Rio Reservoir			(inches)	
							Daily	Cumul.		
Feb. 19	0	309	619	85	95	0	1,592	2,700	0	2.50
20	0	303	1,006	85	372	0	1,634	3,400	0	2.50
21	0	210	1,006	85	445	0	1,954	3,700	0	2.50
22	0	186	1,002	85	408	0	1,819	3,500	0	2.50
23	0	186	1,001	85	472	0	1,756	3,500	.17	2.67
24	0	186	996	85	398	0	1,735	3,400	0	2.67
25	0	186	998	85	0	0	1,731	3,000	0	2.67

1. Release directed to maintain a flow at Montague of 1,750 cfs.

2. Includes conservation release of 60 cfs from Rio Reservoir.

Diversions by New Jersey through the Delaware and Raritan Canal February 19 - 25, 2007, averaged 98.4 mgd. The average diversion for the 30-day period ending February 25, 2007 was 95.8 mgd and the maximum daily diversion was 104 mg on February 21, 2007.

OFFICE OF THE DELAWARE RIVER MASTER, MILFORD, PA.

Web address: <http://water.usgs.gov/orh/nrwww/odrm>

Summary river data for February 26 to March 4, 2007 (preliminary data-subject to revision)

RESERVOIR OPERATION DATA

Millions of gallons - 24 hour period, local time

Date	Discharge to river			Diversions to New York City water supply			
	Pepacton	Cannonsville	Neversink	Pepacton	Cannonsville	Neversink	Average June 1, 2006 to date
	release begin 1200	release end 2400	release begin 1500	beginning 0800	beginning 0800	beginning 0800	
Feb. 26	120	587	55	351	224	110	453
27	120	434	55	351	198	107	454
28	120	306	55	351	200	113	455
Mar. 1	120	290	55	350	200	112	455
2	120	290	55	352	125	107	456
3	120	289	55	353	0	0	456
4	120	289	55	354	12	0	455

Pepacton Reservoir (P):	Available storage Mar. 5, 2007 (0800)	122.894 billion gals.	87.7 % (elev. 1,270.29 ft.)
	Spillway crest elevation 1,280.00 ft.	140.190 billion gallons.	
Cannonsville Reservoir (C):	Available storage Mar. 5, 2007 (0800)	80.447 billion gals.	84.1 % (elev. 1,139.69 ft.)
	Spillway crest elevation 1,150.00 ft.	95.706 billion gallons.	
Neversink Reservoir (N):	Available storage Mar. 5, 2007 (0800)	30.616 billion gals.	87.6 % (elev. 1,430.92 ft.)
	Spillway crest elevation 1,440.00 ft.	34.941 billion gallons.	
Combined contents, PCN:	Available storage Mar. 5, 2007 (0800)	233.957 billion gals.	86.4 %
	Combined capacity at spillway level.	270.837 billion gallons.	
Lake Wallenpaupack:	Available storage Mar. 4, 2007 (2400)	16.610 billion gals.	46.9 % (elev. 1,179.7 ft.)
	Spillway crest elevation 1,190.00 ft.	35.451 billion gallons.	

SEGREGATION OF FLOW, DELAWARE RIVER AT MONTAGUE AND
PRECIPITATION IN UPPER DELAWARE RIVER BASIN

Discharge in cubic feet per second, local time as routed to Montague

Date	Releases from N.Y.C. Reservoirs				Power releases		Computed uncon- trolled ²	Total Discharge	Precipitation	
	Directed release ¹	Pepacton	Cannons- ville	Never- sink	Wallen- paupack	Rio Reservoir			(inches)	
							Daily	Cumul.		
Feb. 26	0	186	1,001	85	51	0	1,777	3,100	.26	2.93
27	0	186	998	85	688	0	1,943	3,900	.03	2.96
28	0	186	908	85	749	0	1,972	3,900	0	2.96
Mar. 1	0	186	671	85	1,351	0	2,107	4,400	0	0
2	0	186	473	85	1,689	0	5,067	7,500	.80	.80
3	0	186	449	85	1,295	0	5,485	7,500	.11	.91
4	0	186	449	85	668	0	5,412	6,800	.01	.92

1. Release directed to maintain a flow at Montague of 1,750 cfs.

2. Includes conservation release of 60 cfs from Rio Reservoir.

Diversions by New Jersey through the Delaware and Raritan Canal February 26 to March 4, 2007, averaged 75.9 mgd. The average diversion for the 30-day period ending March 4, 2007 was 92.0 mgd and the maximum daily diversion was 104 mg on February 21, 2007.

OFFICE OF THE DELAWARE RIVER MASTER, MILFORD, PA.

Web address: <http://water.usgs.gov/orh/nrwww/odrm>

Summary river data for March 5 - 11, 2007 (preliminary data-subject to revision)

RESERVOIR OPERATION DATA

Millions of gallons - 24 hour period, local time

Date	Discharge to river			Diversions to New York City water supply			
	Pepacton	Cannonsville	Neversink	Pepacton	Cannonsville	Neversink	Average
	release begin 1200	release end 2400	release begin 1500	beginning 0800	beginning 0800	beginning 0800	June 1, 2006 to date
Mar. 5	120	289	55	350	136	109	456
6	120	352	55	354	135	107	456
7	120	600	55	354	135	110	457
8	120	642	55	353	198	109	457
9	120	607	55	350	196	107	458
10	115	489	52	338	39	0	458
11	120	319	55	353	12	0	458

Pepacton Reservoir (P):	Available storage Mar. 12, 2007 (0800)	121.077 billion gals.	86.4 % (elev. 1,269.23 ft.)
	Spillway crest elevation 1,280.00 ft.	140.190 billion gallons.	
Cannonsville Reservoir (C):	Available storage Mar. 12, 2007 (0800)	78.457 billion gals.	82.0 % (elev. 1,138.25 ft.)
	Spillway crest elevation 1,150.00 ft.	95.706 billion gallons.	
Neversink Reservoir (N):	Available storage Mar. 12, 2007 (0800)	30.114 billion gals.	86.2 % (elev. 1,429.82 ft.)
	Spillway crest elevation 1,440.00 ft.	34.941 billion gallons.	
Combined contents, PCN:	Available storage Mar.12, 2007 (0800)	229.648 billion gals.	84.8 %
	Combined capacity at spillway level.	270.837 billion gallons.	
Lake Wallenpaupack:	Available storage Mar. 11, 2007 (2400)	16.610 billion gals.	46.9 % (elev. 1,179.7 ft.)
	Spillway crest elevation 1,190.00 ft.	35.451 billion gallons.	

SEGREGATION OF FLOW, DELAWARE RIVER AT MONTAGUE AND
PRECIPITATION IN UPPER DELAWARE RIVER BASIN

Discharge in cubic feet per second, local time as routed to Montague

Date	Releases from N.Y.C. Reservoirs				Power releases		Computed uncon- trolled ²	Total Discharge	Precipitation	
	Directed release ¹	Pepacton	Cannons- ville	Never- sink	Wallen- paupack	Rio Reservoir			(inches)	
							Daily	Cumul.		
Mar. 5	0	186	447	85	382	0	5,100	6,200	0	.92
6	0	186	447	85	303	0	3,579	4,600	.02	.94
7	0	186	447	85	544	0	2,638	3,900	.02	.96
8	0	186	545	85	367	0	2,417	3,600	0	.96
9	0	186	928	85	268	0	2,633	4,100	0	.96
10	0	186	993	85	215	0	2,421	3,900	0	.96
11	0	186	939	85	0	0	2,490	3,700	.22	1.18

1. Release directed to maintain a flow at Montague of 1,750 cfs.

2. Includes conservation release of 60 cfs from Rio Reservoir.

Diversions by New Jersey through the Delaware and Raritan Canal March 5 - 11, 2007, averaged 85.4 mgd. The average diversion for the 30-day period ending March 11, 2007 was 90.2 mgd and the maximum daily diversion was 104 mgd on February 21, 2007.

OFFICE OF THE DELAWARE RIVER MASTER, MILFORD, PA.

Web address: <http://water.usgs.gov/orh/nrwww/odrm>

Summary river data for March 12 - 18, 2007 (preliminary data-subject to revision)

RESERVOIR OPERATION DATA

Millions of gallons - 24 hour period, local time

Date	Discharge to river			Diversions to New York City water supply			
	Pepacton	Cannonsville	Neversink	Pepacton	Cannonsville	Neversink	Average June 1, 2006 to date
	release begin 1200	release end 2400	release begin 1500	beginning 0800	beginning 0800	beginning 0800	
Mar. 12	120	182	64	353	200	103	458
13	120	165	51	357	199	106	459
14	119	165	52	376	200	104	460
15	65	135	42	6	3	0	458
16	117	118	42	0	0	0	457
17	120	454	42	0	0	0	455
18	125	648	42	0	0	0	453

Pepacton Reservoir (P):	Available storage Mar. 19, 2007 (0800)	130.581 billion gals.	93.1 % (elev. 1,274.69 ft.)
	Spillway crest elevation 1,280.00 ft.	140.190 billion gallons.	
Cannonsville Reservoir (C):	Available storage Mar. 19, 2007 (0800)	92.512 billion gals.	96.7 % (elev. 1,147.90 ft.)
	Spillway crest elevation 1,150.00 ft.	95.706 billion gallons.	
Neversink Reservoir (N):	Available storage Mar. 19, 2007 (0800)	31.466 billion gals.	90.1 % (elev. 1,432.76 ft.)
	Spillway crest elevation 1,440.00 ft.	34.941 billion gallons.	
Combined contents, PCN:	Available storage Mar.19, 2007 (0800)	254.559 billion gals.	94.0 %
	Combined capacity at spillway level.	270.837 billion gallons.	
Lake Wallenpaupack:	Available storage Mar. 18, 2007 (2400)	20.690 billion gals.	58.4 % (elev. 1,182.0 ft.)
	Spillway crest elevation 1,190.00 ft.	35.451 billion gallons.	

SEGREGATION OF FLOW, DELAWARE RIVER AT MONTAGUE AND
PRECIPITATION IN UPPER DELAWARE RIVER BASIN

Discharge in cubic feet per second, local time as routed to Montague

Date	Releases from N.Y.C. Reservoirs				Power releases		Computed uncon- trolled ²	Total Discharge	Precipitation	
	Directed release ¹	Pepacton	Cannons- ville	Never- sink	Wallen- paupack	Rio Reservoir			(inches)	
							Daily	Cumul.		
Mar. 12	0	186	756	80	23	0	3,055	4,100	0	1.18
13	0	178	493	85	179	0	3,665	4,600	0	1.18
14	0	186	282	99	175	0	5,058	5,800	0	1.18
15	0	186	255	79	206	78	14,496	15,300	.18	1.36
16	0	186	255	80	185	305	25,089	26,100	.11	1.47
17	0	184	209	65	243	571	14,828	16,100	1.32	2.79
18	0	101	183	65	0	759	11,692	12,800	.01	2.80

1. Release directed to maintain a flow at Montague of 1,750 cfs.

2. Includes conservation release of 60 cfs from Rio Reservoir.

Diversions by New Jersey through the Delaware and Raritan Canal March 12 - 18, 2007, averaged 85.3 mgd. The average diversion for the 30-day period ending March 18, 2007 was 87.2 mgd and the maximum daily diversion was 104 mgd on February 21, 2007.

OFFICE OF THE DELAWARE RIVER MASTER, MILFORD, PA.

Web address: <http://water.usgs.gov/orh/nrwww/odrm>

Summary river data for March 19 - 25, 2007 (preliminary data-subject to revision)

RESERVOIR OPERATION DATA

Millions of gallons - 24 hour period, local time

Date	Discharge to river				Diversions to New York City water supply			
	Pepacton	Cannonsville		Neversink	Pepacton	Cannonsville	Neversink	Average
	release begin 1200	release end 2400	spill begin 0800	release begin 1500	beginning 0800	beginning 0800	beginning 0800	June 1, 2006 to date
Mar. 19	365	649	0	42	143	0	61	453
20	452	648	0	106	152	0	63	452
21	452	647	0	123	151	0	61	451
22	452	644	0	123	312	0	58	451
23	452	646	82	122	351	0	50	450
24	452	650	602	123	351	0	0	450
25	452	599	1,591	122	351	0	0	450

Pepacton Reservoir (P):	Available storage Mar. 26, 2007 (0800)	135.874 billion gals.	96.9 % (elev. 1,277.64 ft.)
	Spillway crest elevation 1,280.00 ft.	140.190 billion gallons.	
Cannonsville Reservoir (C):	Available storage Mar. 26, 2007 (0800)	99.697 billion gals.	104.2 % (elev. 1,152.48 ft.)
	Spillway crest elevation 1,150.00 ft.	95.706 billion gallons.	
Neversink Reservoir (N):	Available storage Mar. 26, 2007 (0800)	32.241 billion gals.	92.3 % (elev. 1,434.41 ft.)
	Spillway crest elevation 1,440.00 ft.	34.941 billion gallons.	
Combined contents, PCN:	Available storage Mar.26, 2007 (0800)	267.812 billion gals.	98.9 %
	Combined capacity at spillway level.	270.837 billion gallons.	
Lake Wallenpaupack:	Available storage Mar. 25, 2007 (2400)	23.395 billion gals.	66.0 % (elev. 1,183.5 ft.)
	Spillway crest elevation 1,190.00 ft.	35.451 billion gallons.	

SEGREGATION OF FLOW, DELAWARE RIVER AT MONTAGUE AND
PRECIPITATION IN UPPER DELAWARE RIVER BASIN

Discharge in cubic feet per second, local time as routed to Montague

Date	Releases from N.Y.C. Reservoirs				Power releases		Computed uncon- trolled ²	Total Discharge	Precipitation	
	Directed release ¹	Pepacton	Cannons- ville	Never- sink	Wallen- paupack	Rio Reservoir			(inches)	
							Daily	Cumul.		
Mar. 19	0	181	702	65	4	759	8,889	10,600	0	2.80
20	0	186	1,002	65	199	748	7,070	9,270	.30	3.10
21	0	193	1,004	65	264	138	6,476	8,140	0	3.10
22	0	565	1,002	164	774	78	5,817	8,400	0	3.10
23	0	699	1,001	190	834	312	10,864	13,900	.05	3.15
24	0	699	996	190	832	248	15,135	18,100	0	3.15
25	0	699	999	189	549	255	18,009	20,700	.30	3.45

1. Release directed to maintain a flow at Montague of 1,750 cfs.

2. Includes conservation release of 60 cfs from Rio Reservoir.

Diversions by New Jersey through the Delaware and Raritan Canal March 19 - 25, 2007, averaged 81.1 mgd. The average diversion for the 30-day period ending March 25, 2007 was 83.1 mgd and the maximum daily diversion was 99 mg on February 24, 2007.

OFFICE OF THE DELAWARE RIVER MASTER, MILFORD, PA.

Web address: <http://water.usgs.gov/orh/nrwww/odrm>

Summary river data for March 26 - April 1, 2007 (preliminary data-subject to revision)

RESERVOIR OPERATION DATA

Millions of gallons - 24 hour period, local time

Date	Discharge to river						Diversions to New York City water supply			
	Pepacton		Cannonsville		Neversink		Pepacton	Cannonsville	Neversink	Average June 1, 2006 to date
	release begin 1200	spill begin 0800	release end 2400	spill begin 0800	release begin 1500	spill begin 0800	beginning 0800	beginning 0800	beginning 0800	
Mar. 26	452	0	152	2,299	123	0	36	0	0	448
27	452	5	51	3,072	114	0	0	0	0	447
28	318	761	29	3,598	66	0	0	0	0	445
29	28	1,573	28	3,215	118	0	0	0	0	444
30	45	1,494	30	2,576	118	0	0	0	0	443
31	307	1,161	424	1,896	116	108	0	0	0	441
Apr. 1	452	754	635	1,310	110	235	0	0	0	440

Pepacton Reservoir (P):	Available storage Apr. 2, 2007 (0800)	141.227 billion gals. 100.7 % (elev. 1,280.56 ft.)
	Spillway crest elevation 1,280.00 ft.	140.190 billion gallons.
Cannonsville Reservoir (C):	Available storage Apr. 2, 2007 (0800)	98.523 billion gals. 102.9 % (elev. 1,151.75 ft.)
	Spillway crest elevation 1,150.00 ft.	95.706 billion gallons.
Neversink Reservoir (N):	Available storage Apr. 2, 2007 (0800)	35.125 billion gals. 100.5 % (elev. 1,440.37 ft.)
	Spillway crest elevation 1,440.00 ft.	34.941 billion gallons.
Combined contents, PCN:	Available storage Apr.2, 2007 (0800)	274.875 billion gals. 101.5 %
	Combined capacity at spillway level.	270.837 billion gallons.
Lake Wallenpaupack:	Available storage Apr. 1, 2007 (2400)	26.315 billion gals. 74.2 % (elev. 1,185.1 ft.)
	Spillway crest elevation 1,190.00 ft.	35.451 billion gallons.

SEGREGATION OF FLOW, DELAWARE RIVER AT MONTAGUE AND
PRECIPITATION IN UPPER DELAWARE RIVER BASIN

Discharge in cubic feet per second, local time as routed to Montague

Date	Releases from N.Y.C. Reservoirs				Power releases		Computed uncon- trolled ²	Total Discharge	Precipitation	
	Directed release ¹	Pepacton	Cannons- ville	Never- sink	Wallen- paupack	Rio Reservoir			(inches)	
							Daily	Cumul.		
Mar. 26	0	699	1,006	190	229	447	21,829	24,400	0	3.45
27	0	699	927	189	349	766	23,470	26,400	.16	3.61
28	0	699	235	190	469	766	31,641	34,000	0	3.61
29	0	699	79	176	611	759	28,276	30,600	0	3.61
30	0	699	45	102	786	770	22,198	24,600	0	3.61
31	0	492	43	183	780	770	18,132	20,400	0	3.61
Apr. 1	0	43	46	183	642	770	16,116	17,800	0	0

1. Release directed to maintain a flow at Montague of 1,750 cfs.

2. Includes conservation release of 60 cfs from Rio Reservoir.

Diversions by New Jersey through the Delaware and Raritan Canal March 26 - April 1, 2007, averaged 88.3 mgd. The average diversion for the 30-day period ending April 1, 2007 was 84.3 mgd and the maximum daily diversion was 93 mg on March 15, 2007.

OFFICE OF THE DELAWARE RIVER MASTER, MILFORD, PA.

Web address: <http://water.usgs.gov/orh/nrwww/odrm>

Summary river data for April 2 - 8, 2007 (preliminary data-subject to revision)

RESERVOIR OPERATION DATA

Millions of gallons - 24 hour period, local time

Date	Discharge to river						Diversions to New York City water supply			
	Pepacton		Cannonsville		Neversink		Pepacton	Cannonsville	Neversink	Average June 1, 2006 to date
	release begin 1200	spill begin 0800	release end 2400	spill begin 0800	release begin 1500	spill begin 0800	beginning 0800	beginning 0800	beginning 0800	
Apr. 2	452	475	640	946	2	308	300	58	0	439
3	452	264	647	701	98	295	311	0	165	439
4	452	250	646	630	78	294	353	0	16	439
5	452	235	646	598	102	301	353	0	94	439
6	452	145	647	524	118	109	353	0	94	439
7	452	63	647	417	122	130	354	0	0	439
8	452	14	646	312	122	121	353	0	0	439

Pepacton Reservoir (P):	Available storage Apr. 9, 2007 (0800)	140.098 billion gals.	99.9 % (elev. 1,279.95 ft.)
	Spillway crest elevation 1,280.00 ft.	140.190 billion gallons.	
Cannonsville Reservoir (C):	Available storage Apr. 9, 2007 (0800)	96.848 billion gals.	101.2 % (elev. 1,150.71 ft.)
	Spillway crest elevation 1,150.00 ft.	95.706 billion gallons.	
Neversink Reservoir (N):	Available storage Apr. 9, 2007 (0800)	35.045 billion gals.	100.3 % (elev. 1,440.21 ft.)
	Spillway crest elevation 1,440.00 ft.	34.941 billion gallons.	
Combined contents, PCN:	Available storage Apr.9, 2007 (0800)	271.991 billion gals.	100.4 %
	Combined capacity at spillway level.	270.837 billion gallons.	
Lake Wallenpaupack:	Available storage Apr. 8, 2007 (2400)	24.672 billion gals.	69.6 % (elev. 1,184.2 ft.)
	Spillway crest elevation 1,190.00 ft.	35.451 billion gallons.	

SEGREGATION OF FLOW, DELAWARE RIVER AT MONTAGUE AND
PRECIPITATION IN UPPER DELAWARE RIVER BASIN

Discharge in cubic feet per second, local time as routed to Montague

Date	Releases from N.Y.C. Reservoirs				Power releases		Computed uncon- trolled ²	Total Discharge	Precipitation	
	Directed release ¹	Pepacton	Cannons- ville	Never- sink	Wallen- paupack	Rio Reservoir			(inches)	
							Daily	Cumul.		
Apr. 2	0	70	656	179	720	770	14,505	16,900	.23	.23
3	0	475	982	170	827	770	12,176	15,400	.01	.24
4	0	699	990	3	827	770	10,911	14,200	0	.24
5	0	699	1,001	152	1,694	755	12,299	16,600	.53	.77
6	0	699	999	121	1,599	762	10,620	14,800	0	.77
7	0	699	999	158	1,254	762	8,528	12,400	0	.77
8	0	699	1,001	183	742	762	7,313	10,700	0	.77

1. Release directed to maintain a flow at Montague of 1,750 cfs.

2. Includes conservation release of 60 cfs from Rio Reservoir.

Diversions by New Jersey through the Delaware and Raritan Canal April 2 - 8, 2007, averaged 86.7 mgd. The average diversion for the 30-day period ending April 8, 2007 was 85.4 mgd and the maximum daily diversion was 93 mg on March 15, 2007.

OFFICE OF THE DELAWARE RIVER MASTER, MILFORD, PA.

Web address: <http://water.usgs.gov/orh/nrwww/odrm>

Summary river data for April 9 - 15, 2007 (preliminary data-subject to revision)

RESERVOIR OPERATION DATA

Millions of gallons - 24 hour period, local time

Date	Discharge to river						Diversions to New York City water supply			
	Pepacton		Cannonsville		Neversink		Pepacton	Cannonsville	Neversink	Average June 1, 2006 to date
	release begin 1200	spill begin 0800	release end 2400	spill begin 0800	release begin 1500	spill begin 0800	beginning 0800	beginning 0800	beginning 0800	
Apr. 9	452	0	646	239	101	100	407	0	0	439
10	452	0	645	168	0	121	291	0	0	438
11	452	0	646	87	0	143	351	104	0	438
12	452	0	645	70	0	180	506	0	0	438
13	452	0	646	123	105	105	333	0	129	439
14	452	0	648	127	123	4	300	0	154	439
15	382	154	648	285	71	857	121	0	98	438

Pepacton Reservoir (P):	Available storage Apr. 16, 2007 (0800)	141.783 billion gals. 101.1% (elev. 1,280.86 ft.)
	Spillway crest elevation 1,280.00 ft.	140.190 billion gallons.
Cannonsville Reservoir (C):	Available storage Apr. 16, 2007 (0800)	97.798 billion gals. 102.2% (elev. 1,151.30 ft.)
	Spillway crest elevation 1,150.00 ft.	95.706 billion gallons.
Neversink Reservoir (N):	Available storage Apr. 16, 2007 (0800)	35.983 billion gals. 103.0% (elev. 1,442.09 ft.)
	Spillway crest elevation 1,440.00 ft.	34.941 billion gallons.
Combined contents, PCN:	Available storage Apr.16, 2007 (0800)	275.564 billion gals. 101.7%
	Combined capacity at spillway level.	270.837 billion gallons.
Lake Wallenpaupack:	Available storage Apr. 15, 2007 (2400)	25.585 billion gals. 72.2% (elev. 1,184.7 ft.)
	Spillway crest elevation 1,190.00 ft.	35.451 billion gallons.

SEGREGATION OF FLOW, DELAWARE RIVER AT MONTAGUE AND
PRECIPITATION IN UPPER DELAWARE RIVER BASIN

Discharge in cubic feet per second, local time as routed to Montague

Date	Releases from N.Y.C. Reservoirs				Power releases		Computed uncon- trolled ²	Total Discharge	Precipitation	
	Directed release ¹	Pepacton	Cannons- ville	Never- sink	Wallen- paupack	Rio Reservoir			(inches)	
							Daily	Cumul.		
Apr. 9	0	699	1,001	189	571	709	6,431	9,600	0	.77
10	0	699	999	189	697	408	5,558	8,550	0	.77
11	0	699	999	156	507	504	4,885	7,750	0	.77
12	0	699	998	0	492	369	5,032	7,590	.31	1.08
13	0	699	999	0	528	734	6,640	9,600	.23	1.31
14	0	699	998	0	554	702	6,097	9,050	0	1.31
15	0	699	999	162	0	170	8,470	10,500	.44	1.75

1. Release directed to maintain a flow at Montague of 1,750 cfs.

2. Includes conservation release from Rio Reservoir and spills from Pepacton, Cannonsville and Neversink Reservoirs.

Diversions by New Jersey through the Delaware and Raritan Canal April 9 - 15, 2007, averaged 59.1 mgd. The average diversion for the 30-day period ending April 15, 2007 was 78.8 mgd and the maximum daily diversion was 94 mg on April 10 and 11, 2007.

OFFICE OF THE DELAWARE RIVER MASTER, MILFORD, PA.

Web address: <http://water.usgs.gov/orh/nrwww/odrm>

Summary river data for April 16 - 22, 2007 (preliminary data-subject to revision)

RESERVOIR OPERATION DATA

Millions of gallons - 24 hour period, local time

Date	Discharge to river						Diversions to New York City water supply			
	Pepacton		Cannonsville		Neversink		Pepacton	Cannonsville	Neversink	Average June 1, 2006 to date
	release begin 1200	spill begin 0800	release end 2400	spill begin 0800	release begin 1500	spill begin 0800	beginning 0800	beginning 0800	beginning 0800	
Apr. 16	23	2,884	651	1,354	17	2,696	0	0	0	436
17	23	3,605	464	2,338	111	949	0	0	0	435
18	23	3,011	33	2,836	123	538	0	0	0	434
19	23	2,564	29	3,167	123	427	0	0	0	432
20	23	2,393	29	3,247	123	427	0	0	0	431
21	23	2,040	29	2,848	123	416	315	0	0	431
22	23	1,680	63	2,365	123	432	399	0	0	431

Pepacton Reservoir (P):	Available storage Apr. 23, 2007 (0800)	141.987 billion gals.	101.3% (elev. 1,280.97 ft.)
	Spillway crest elevation 1,280.00 ft.	140.190 billion gallons.	
Cannonsville Reservoir (C):	Available storage Apr. 23, 2007 (0800)	99.826 billion gals.	104.3% (elev. 1,152.56 ft.)
	Spillway crest elevation 1,150.00 ft.	95.706 billion gallons.	
Neversink Reservoir (N):	Available storage Apr. 23, 2007 (0800)	35.209 billion gals.	100.8% (elev. 1,440.54 ft.)
	Spillway crest elevation 1,440.00 ft.	34.941 billion gallons.	
Combined contents, PCN:	Available storage Apr. 23, 2007 (0800)	277.022 billion gals.	102.3%
	Combined capacity at spillway level.	270.837 billion gallons.	
Lake Wallenpaupack:	Available storage Apr. 22, 2007 (2400)	28.143 billion gals.	79.4% (elev. 1,186.1 ft.)
	Spillway crest elevation 1,190.00 ft.	35.451 billion gallons.	

SEGREGATION OF FLOW, DELAWARE RIVER AT MONTAGUE AND
PRECIPITATION IN UPPER DELAWARE RIVER BASIN

Discharge in cubic feet per second, local time as routed to Montague

Date	Releases from N.Y.C. Reservoirs				Power releases		Computed uncon- trolled ²	Total Discharge	Precipitation	
	Directed release ¹	Pepacton	Cannons- ville	Never- sink	Wallen- paupack	Rio Reservoir			(inches)	
							Daily	Cumul.		
Apr. 16	0	699	1,002	190	1,447	752	52,710	56,800	2.56	4.31
17	0	699	1,002	110	1,722	766	49,201	53,500	.45	4.76
18	0	591	1,007	26	1,724	766	34,286	38,400	.01	4.77
19	0	36	718	172	1,724	766	28,084	31,500	0	4.77
20	0	36	51	190	1,724	766	25,433	28,200	0	4.77
21	0	36	45	190	648	762	22,019	23,700	0	4.77
22	0	36	45	190	0	759	19,170	20,200	0	4.77

1. Release directed to maintain a flow at Montague of 1,750 cfs.

2. Includes conservation release from Rio Reservoir and spills from Pepacton, Cannonsville and Neversink Reservoirs.

Diversions by New Jersey through the Delaware and Raritan Canal April 16 - 22, 2007, averaged 24.1 mgd. The average diversion for the 30-day period ending April 22, 2007 was 65.9 mgd and the maximum daily diversion was 95 mg on April 22, 2007.

OFFICE OF THE DELAWARE RIVER MASTER, MILFORD, PA.

Web address: <http://water.usgs.gov/orh/nrwww/odrm>

Summary river data for April 23 - 29, 2007 (preliminary data-subject to revision)

RESERVOIR OPERATION DATA

Millions of gallons - 24 hour period, local time

Date	Discharge to river						Diversions to New York City water supply			
	Pepacton		Cannonsville		Neversink		Pepacton	Cannonsville	Neversink	Average June 1, 2006 to date
	release begin 1200	spill begin 0800	release end 2400	spill begin 0800	release begin 1500	spill begin 0800	beginning 0800	beginning 0800	beginning 0800	
Apr. 23	71	1,350	378	1,795	97	381	462	0	183	431
24	243	1,043	514	1,382	97	171	499	0	254	432
25	447	697	647	1,045	110	82	500	0	253	433
26	452	409	647	866	107	48	500	0	251	434
27	452	294	647	628	123	15	93	189	345	435
28	452	352	646	409	120	0	0	298	399	436
29	452	338	645	245	57	0	0	298	399	436

Pepacton Reservoir (P):	Available storage Apr. 30, 2007 (0800)	140.838 billion gals.	100.5% (elev. 1,280.35 ft.)
	Spillway crest elevation 1,280.00 ft.	140.190 billion gallons.	
Cannonsville Reservoir (C):	Available storage Apr. 30, 2007 (0800)	96.591 billion gals.	100.9 % (elev. 1,150.55 ft.)
	Spillway crest elevation 1,150.00 ft.	95.706 billion gallons.	
Neversink Reservoir (N):	Available storage Apr. 30, 2007 (0800)	34.463 billion gals.	98.6 % (elev. 1,439.03 ft.)
	Spillway crest elevation 1,440.00 ft.	34.941 billion gallons.	
Combined contents, PCN:	Available storage Apr. 30, 2007 (0800)	271.892 billion gals.	100.4%
	Combined capacity at spillway level.	270.837 billion gallons.	
Lake Wallenpaupack:	Available storage Apr. 29, 2007 (2400)	27.957 billion gals.	78.9 % (elev. 1,186.0 ft.)
	Spillway crest elevation 1,190.00 ft.	35.451 billion gallons.	

SEGREGATION OF FLOW, DELAWARE RIVER AT MONTAGUE AND
PRECIPITATION IN UPPER DELAWARE RIVER BASIN

Discharge in cubic feet per second, local time as routed to Montague

Date	Releases from N.Y.C. Reservoirs				Power releases		Computed uncon- trolled ²	Total Discharge	Precipitation	
	Directed release ¹	Pepacton	Cannons- ville	Never- sink	Wallen- paupack	Rio Reservoir			(inches)	
							Daily	Cumul.		
Apr. 23	0	36	45	190	603	755	16,671	18,300	0	4.77
24	0	36	97	190	1,724	713	13,740	16,500	.01	4.78
25	0	36	585	150	1,151	383	11,095	13,400	0	4.78
26	0	110	795	150	392	493	10,760	12,700	.37	5.15
27	0	376	1,001	170	427	362	9,564	11,900	.15	5.30
28	0	692	1,001	166	317	532	7,992	10,700	.02	5.32
29	0	699	1,001	190	0	748	6,942	9,580	.04	5.36

1. Release directed to maintain a flow at Montague of 1,750 cfs.

2. Includes conservation release from Rio Reservoir and spills from Pepacton, Cannonsville, and Neversink Reservoirs.

Diversions by New Jersey through the Delaware and Raritan Canal April 23 - 29, 2007, averaged 84.0 mgd. The average diversion for the 30-day period ending April 29, 2007 was 65.4 mgd and the maximum daily diversion was 96 mg on April 26, 2007.

OFFICE OF THE DELAWARE RIVER MASTER, MILFORD, PA.

Web address: <http://water.usgs.gov/orh/nrwww/odrm>

Summary river data for April 30 - May 6, 2007 (preliminary data-subject to revision)

RESERVOIR OPERATION DATA

Millions of gallons - 24 hour period, local time

Date	Discharge to river					Diversions to New York City water supply			
	Pepacton		Cannonsville		Neversink	Pepacton	Cannonsville	Neversink	Average June 1, 2006 to date
	release begin 1200	spill begin 0800	release end 2400	spill begin 0800	release begin 1500	beginning 0800	beginning 0800	beginning 0800	
Apr. 30	452	213	645	94	42	0	288	394	437
May 1	452	228	644	64	43	0	99	121	436
2	326	190	586	53	48	0	250	113	436
3	139	188	426	29	48	0	455	195	437
4	66	170	254	14	48	239	360	86	438
5	65	112	128	0	48	401	299	0	438
6	65	68	92	0	48	392	299	0	439

Pepacton Reservoir (P):	Available storage May 7, 2007 (0800)	140.283 billion gals.	100.1% (elev. 1,280.05 ft.)
	Spillway crest elevation 1,280.00 ft.	140.190 billion gallons.	
Cannonsville Reservoir (C):	Available storage May 7, 2007 (0800)	95.600 billion gals.	99.9 % (elev. 1,149.93 ft.)
	Spillway crest elevation 1,150.00 ft.	95.706 billion gallons.	
Neversink Reservoir (N):	Available storage May 7, 2007 (0800)	34.508 billion gals.	98.8 % (elev. 1,439.12 ft.)
	Spillway crest elevation 1,440.00 ft.	34.941 billion gallons.	
Combined contents, PCN:	Available storage May 7, 2007 (0800)	270.391 billion gals.	99.8%
	Combined capacity at spillway level.	270.837 billion gallons.	
Lake Wallenpaupack:	Available storage May 6, 2007 (2400)	27.957 billion gals.	78.9 % (elev. 1,186.0 ft.)
	Spillway crest elevation 1,190.00 ft.	35.451 billion gallons.	

SEGREGATION OF FLOW, DELAWARE RIVER AT MONTAGUE AND
PRECIPITATION IN UPPER DELAWARE RIVER BASIN

Discharge in cubic feet per second, local time as routed to Montague

Date	Releases from N.Y.C. Reservoirs				Power releases		Computed uncon- trolled ²	Total Discharge	Precipitation	
	Directed release ¹	Pepacton	Cannons- ville	Never- sink	Wallen- paupack	Rio Reservoir			(inches)	
							Daily	Cumul.		
Apr. 30	0	699	999	186	64	741	6,361	9,050	.01	5.37
May 1	0	699	998	88	512	738	5,585	8,620	0	0
2	0	699	998	65	661	727	4,610	7,760	.17	.17
3	0	699	996	67	360	716	4,422	7,260	0	.17
4	0	699	907	74	371	262	3,717	6,030	0	.17
5	0	504	659	74	240	305	3,268	5,050	0	.17
6	0	215	393	74	0	309	3,339	4,330	0	.17

1. Release directed to maintain a flow at Montague of 1,750 cfs.

2. Includes conservation release from Rio Reservoir and spills from Pepacton and Cannonsville Reservoirs.

Diversions by New Jersey through the Delaware and Raritan Canal April 30 - May 6, 2007, averaged 87.1 mgd. The average diversion for the 30-day period ending May 6, 2007 was 65.3 mgd and the maximum daily diversion was 96 mg on April 26, 2007.

OFFICE OF THE DELAWARE RIVER MASTER, MILFORD, PA.

Web address: <http://water.usgs.gov/orh/nrwww/odrm>

Summary river data for May 7 - 13, 2007 (preliminary data-subject to revision)

RESERVOIR OPERATION DATA

Millions of gallons - 24 hour period, local time

Date	Discharge to river					Diversions to New York City water supply			
	Pepacton		Cannonsville		Neversink	Pepacton	Cannonsville	Neversink	Average June 1, 2006 to date
	release begin 1200	spill begin 0800	release end 2400	spill begin 0800	release begin 1500	beginning 0800	beginning 0800	beginning 0800	
May 7	65	34	92	0	48	399	299	99	440
8	65	0	85	0	48	399	299	91	441
9	73	0	78	0	57	399	299	100	442
10	75	0	85	0	58	372	254	100	443
11	75	0	78	10	58	401	298	101	444
12	75	0	75	22	58	400	298	0	445
13	75	0	70	23	58	401	298	0	446

Pepacton Reservoir (P):	Available storage May 14, 2007 (0800)	139.472 billion gals.	99.5% (elev. 1,279.61 ft.)
	Spillway crest elevation 1,280.00 ft.	140.190 billion gallons.	
Cannonsville Reservoir (C):	Available storage May 14, 2007 (0800)	95.931 billion gals.	100.2 % (elev. 1,150.14 ft.)
	Spillway crest elevation 1,150.00 ft.	95.706 billion gallons.	
Neversink Reservoir (N):	Available storage May 14, 2007 (0800)	34.538 billion gals.	98.8 % (elev. 1,439.18 ft.)
	Spillway crest elevation 1,440.00 ft.	34.941 billion gallons.	
Combined contents, PCN:	Available storage May 14, 2007 (0800)	269.941 billion gals.	99.7%
	Combined capacity at spillway level.	270.837 billion gallons.	
Lake Wallenpaupack:	Available storage May 13, 2007 (2400)	28.328 billion gals.	79.9 % (elev. 1,186.2 ft.)
	Spillway crest elevation 1,190.00 ft.	35.451 billion gallons.	

SEGREGATION OF FLOW, DELAWARE RIVER AT MONTAGUE AND
PRECIPITATION IN UPPER DELAWARE RIVER BASIN

Discharge in cubic feet per second, local time as routed to Montague

Date	Releases from N.Y.C. Reservoirs				Power releases		Computed uncon- trolled ²	Total Discharge	Precipitation	
	Directed release ¹	Pepacton	Cannons- ville	Never- sink	Wallen- paupack	Rio Reservoir			(inches)	
							Daily	Cumul.		
May 7	0	102	198	74	0	316	3,130	3,820	0	.17
8	0	101	142	74	237	14	3,022	3,590	0	.17
9	0	101	142	74	247	14	2,702	3,280	0	.17
10	0	101	131	74	230	99	2,535	3,170	0	.17
11	0	101	121	88	253	234	2,813	3,610	.52	.69
12	0	113	131	90	153	174	3,759	4,420	0	.69
13	0	116	121	90	0	113	3,490	3,930	.04	.73

1. Release directed to maintain a flow at Montague of 1,750 cfs.

2. Includes conservation release from Rio Reservoir and spills from Pepacton and Cannonsville Reservoirs.

Diversions by New Jersey through the Delaware and Raritan Canal May 7 - 13, 2007, averaged 93.7 mgd. The average diversion for the 30-day period ending May 13, 2007 was 67.1 mgd and the maximum daily diversion was 97 mg on May 10, 2007.

OFFICE OF THE DELAWARE RIVER MASTER, MILFORD, PA.

Web address: <http://water.usgs.gov/orh/nrwww/odrm>

Summary river data for May 14 - 20, 2007 (preliminary data-subject to revision)

RESERVOIR OPERATION DATA

Millions of gallons - 24 hour period, local time

Date	Discharge to river				Diversions to New York City water supply			
	Pepacton	Cannonsville		Neversink	Pepacton	Cannonsville	Neversink	Average
	release begin 1200	release end 2400	spill begin 0800	release begin 1500	beginning 0800	beginning 0800	beginning 0800	June 1, 2006 to date
May 14	75	70	21	58	401	298	74	447
15	83	74	13	58	56	376	183	447
16	76	79	3	58	368	306	63	448
17	75	69	3	58	401	299	90	449
18	75	74	3	69	435	299	91	450
19	75	88	0	70	449	299	0	451
20	72	94	0	66	449	299	0	452

Pepacton Reservoir (P):	Available storage May 21, 2007 (0800)	139.234 billion gals.	99.3% (elev. 1,279.48 ft.)
	Spillway crest elevation 1,280.00 ft.	140.190 billion gallons.	
Cannonsville Reservoir (C):	Available storage May 21, 2007 (0800)	95.615 billion gals.	99.9 % (elev. 1,149.94 ft.)
	Spillway crest elevation 1,150.00 ft.	95.706 billion gallons.	
Neversink Reservoir (N):	Available storage May 21, 2007 (0800)	34.262 billion gals.	98.1 % (elev. 1,438.62 ft.)
	Spillway crest elevation 1,440.00 ft.	34.941 billion gallons.	
Combined contents, PCN:	Available storage May 21, 2007 (0800)	269.111 billion gals.	99.4%
	Combined capacity at spillway level.	270.837 billion gallons.	
Lake Wallenpaupack:	Available storage May 20, 2007 (2400)	28.886 billion gals.	81.5 % (elev. 1,186.5 ft.)
	Spillway crest elevation 1,190.00 ft.	35.451 billion gallons.	

SEGREGATION OF FLOW, DELAWARE RIVER AT MONTAGUE AND
PRECIPITATION IN UPPER DELAWARE RIVER BASIN

Discharge in cubic feet per second, local time as routed to Montague

Date	Releases from N.Y.C. Reservoirs				Power releases		Computed uncon- trolled ²	Total Discharge	Precipitation	
	Directed release ¹	Pepacton	Cannons- ville	Never- sink	Wallen- paupack	Rio Reservoir			(inches)	
							Daily	Cumul.		
May 14	0	116	116	90	0	50	3,028	3,400	0	.73
15	0	116	108	90	0	255	2,661	3,230	0	.73
16	0	116	108	90	0	319	2,467	3,100	0	.73
17	0	116	114	90	0	369	2,481	3,170	.32	1.05
18	0	128	122	90	79	333	2,698	3,450	.01	1.06
19	0	118	107	90	0	78	2,427	2,820	0	1.06
20	0	116	114	107	0	0	2,303	2,640	.11	1.17

1. Release directed to maintain a flow at Montague of 1,750 cfs.

2. Includes conservation release from Rio Reservoir and spill from Cannonsville Reservoir.

Diversions by New Jersey through the Delaware and Raritan Canal May 14 - 20, 2007, averaged 89.1 mgd. The average diversion for the 30-day period ending May 20, 2007 was 88.8 mgd and the maximum daily diversion was 97 mg on May 10, 2007.

OFFICE OF THE DELAWARE RIVER MASTER, MILFORD, PA.

Web address: <http://water.usgs.gov/orh/nrwww/odrm>

Summary river data for May 21 - 27, 2007 (preliminary data-subject to revision)

RESERVOIR OPERATION DATA

Millions of gallons - 24 hour period, local time

Date	Discharge to river			Diversions to New York City water supply			
	Pepacton	Cannonsville	Neversink	Pepacton	Cannonsville	Neversink	Average June 1, 2006 to date
	release begin 1200	release end 2400	release begin 1500	beginning 0800	beginning 0800	beginning 0800	
May 21	78	92	74	449	299	76	453
22	80	98	75	450	299	77	454
23	80	100	75	450	299	75	455
24	88	123	75	450	299	78	456
25	90	165	75	271	299	210	457
26	90	147	75	401	299	164	458
27	90	124	75	401	299	167	459

Pepacton Reservoir (P):	Available storage May 28, 2007 (0800)	137.985 billion gals.	98.4 % (elev. 1,278.80 ft.)
	Spillway crest elevation 1,280.00 ft.	140.190 billion gallons.	
Cannonsville Reservoir (C):	Available storage May 28, 2007 (0800)	94.291 billion gals.	98.5 % (elev. 1,149.07 ft.)
	Spillway crest elevation 1,150.00 ft.	95.706 billion gallons.	
Neversink Reservoir (N):	Available storage May 28, 2007 (0800)	33.456 billion gals.	95.7 % (elev. 1,436.96 ft.)
	Spillway crest elevation 1,440.00 ft.	34.941 billion gallons.	
Combined contents, PCN:	Available storage May 28, 2007 (0800)	265.732 billion gals.	98.1 %
	Combined capacity at spillway level.	270.837 billion gallons.	
Lake Wallenpaupack:	Available storage May 27, 2007 (2400)	28.886 billion gals.	81.5 % (elev. 1,186.5 ft.)
	Spillway crest elevation 1,190.00 ft.	35.451 billion gallons.	

SEGREGATION OF FLOW, DELAWARE RIVER AT MONTAGUE AND
PRECIPITATION IN UPPER DELAWARE RIVER BASIN

Discharge in cubic feet per second, local time as routed to Montague

Date	Releases from N.Y.C. Reservoirs				Power releases		Computed uncon- trolled ²	Total Discharge	Precipitation	
	Directed release ¹	Pepacton	Cannons- ville	Never- sink	Wallen- paupack	Rio Reservoir			(inches)	
							Daily	Cumul.		
May 21	0	116	136	108	0	0	2,240	2,600	.01	1.18
22	0	116	145	102	0	14	2,163	2,540	0	1.18
23	0	111	142	114	0	46	1,977	2,390	0	1.18
24	0	121	152	116	0	113	1,878	2,380	0	1.18
25	0	124	155	116	0	160	1,755	2,310	0	1.18
26	0	124	190	116	228	96	1,606	2,360	0	1.18
27	265	136	255	116	0	0	1,563	2,070	0	1.18

1. Release directed to maintain a flow at Montague of 1,750 cfs.

2. Includes conservation release from Rio Reservoir.

Diversions by New Jersey through the Delaware and Raritan Canal May 21 - 27, 2007, averaged 94.3 mgd. The average diversion for the 30-day period ending May 27, 2007 was 90.1 mgd and the maximum daily diversion was 97 mg on May 10, 2007.

OFFICE OF THE DELAWARE RIVER MASTER, MILFORD, PA.

Web address: <http://water.usgs.gov/orh/nrwww/odrm>

Summary river data for May 28 - June 3, 2007 (preliminary data-subject to revision)

RESERVOIR OPERATION DATA

Millions of gallons - 24 hour period, local time

Date	Discharge to river			Diversions to New York City water supply			
	Pepacton	Cannonsville	Neversink	Pepacton	Cannonsville	Neversink	Average
	release begin 1200	release end 2400	release begin 1500	beginning 0800	beginning 0800	beginning 0800	June 1, 2006/2007 to date
May 28	90	120	75	401	299	167	460
29	90	131	85	446	299	81	461
30	90	144	75	413	299	52	462
31	91	148	76	400	299	53	463
June 1	90	274	84	367	299	52	718
2	89	238	86	350	299	0	684
3	60	144	80	350	87	0	601

Pepacton Reservoir (P):	Available storage June 4, 2007 (0800)	136.526 billion gals.	97.4 % (elev. 1,278.00 ft.)
	Spillway crest elevation 1,280.00 ft.	140.190 billion gallons.	
Cannonsville Reservoir (C):	Available storage June 4, 2007 (0800)	92.451 billion gals.	96.6 % (elev. 1,147.86 ft.)
	Spillway crest elevation 1,150.00 ft.	95.706 billion gallons.	
Neversink Reservoir (N):	Available storage June 4, 2007 (0800)	32.900 billion gals.	94.2 % (elev. 1,435.80 ft.)
	Spillway crest elevation 1,440.00 ft.	34.941 billion gallons.	
Combined contents, PCN:	Available storage June 4, 2007 (0800)	261.877 billion gals.	96.7 %
	Combined capacity at spillway level.	270.837 billion gallons.	
Lake Wallenpaupack:	Available storage June 3, 2007 (2400)	28.886 billion gals.	81.5 % (elev. 1,186.5 ft.)
	Spillway crest elevation 1,190.00 ft.	35.451 billion gallons.	

SEGREGATION OF FLOW, DELAWARE RIVER AT MONTAGUE AND
PRECIPITATION IN UPPER DELAWARE RIVER BASIN

Discharge in cubic feet per second, local time as routed to Montague

Date	Releases from N.Y.C. Reservoirs				Power releases		Computed uncon- trolled ²	Total Discharge	Precipitation	
	Directed release ¹	Pepacton	Cannons- ville	Never- sink	Wallen- paupack	Rio Reservoir			(inches)	
							Daily	Cumul.		
May 28	442	139	227	116	0	0	1,548	2,030	.22	1.40
29	219	139	192	116	0	177	1,576	2,200	0	1.40
30	329	139	186	116	0	0	1,599	2,040	0	1.40
31	275	139	203	131	0	0	1,367	1,840	0	1.40
June 1	450	139	223	116	0	0	1,292	1,770	.02	.02
2	293	139	229	118	275	0	1,219	1,980	0	.02
3	678	141	424	130	0	0	1,205	1,900	.23	.25

1. Release directed to maintain a flow at Montague of 1,750 cfs.

2. Includes conservation release from Rio Reservoir.

Diversions by New Jersey through the Delaware and Raritan Canal May 28 - June 3, 2007, averaged 94.3 mgd. The average diversion for the 30-day period ending June 3, 2007 was 92.6 mgd and the maximum daily diversion was 97 mg on May 10, 2007.

OFFICE OF THE DELAWARE RIVER MASTER, MILFORD, PA.

Web address: <http://water.usgs.gov/orh/nrwww/odrm>

Summary river data for June 4 -10, 2007 (preliminary data-subject to revision)

RESERVOIR OPERATION DATA

Millions of gallons - 24 hour period, local time

Date	Discharge to river			Diversions to New York City water supply			
	Pepacton	Cannonsville	Neversink	Pepacton	Cannonsville	Neversink	Average June 1, 2007 to date
	release begin 1200	release end 2400	release begin 1500	beginning 0800	beginning 0800	beginning 0800	
June 4	70	103	80	350	205	0	590
5	71	98	80	399	298	0	611
6	88	106	71	400	298	0	626
7	94	188	75	401	298	0	636
8	95	294	75	436	298	0	648
9	95	268	75	450	298	0	659
10	94	235	75	450	298	0	668

Pepacton Reservoir (P):	Available storage June 11, 2007 (0800)	135.638 billion gals.	96.8 % (elev. 1,277.51 ft.)
	Spillway crest elevation 1,280.00 ft.	140.190 billion gallons.	
Cannonsville Reservoir (C):	Available storage June 11, 2007 (0800)	90.382 billion gals.	94.4 % (elev. 1,146.50 ft.)
	Spillway crest elevation 1,150.00 ft.	95.706 billion gallons.	
Neversink Reservoir (N):	Available storage June 11, 2007 (0800)	32.977 billion gals.	94.4 % (elev. 1,435.96 ft.)
	Spillway crest elevation 1,440.00 ft.	34.941 billion gallons.	
Combined contents, PCN:	Available storage June 11, 2007 (0800)	258.997 billion gals.	95.6 %
	Combined capacity at spillway level.	270.837 billion gallons.	
Lake Wallenpaupack:	Available storage June 10, 2007 (2400)	27.592 billion gals.	77.8 % (elev. 1,185.8 ft.)
	Spillway crest elevation 1,190.00 ft.	35.451 billion gallons.	

SEGREGATION OF FLOW, DELAWARE RIVER AT MONTAGUE AND
PRECIPITATION IN UPPER DELAWARE RIVER BASIN

Discharge in cubic feet per second, local time as routed to Montague

Date	Releases from N.Y.C. Reservoirs				Power releases		Computed uncon- trolled ²	Total Discharge	Precipitation	
	Directed release ¹	Pepacton	Cannons- ville	Never- sink	Wallen- paupack	Rio Reservoir			(inches)	
									Daily	Cumul.
June 4	649	139	368	133	4	14	1,702	2,360	.65	.90
5	0	138	223	124	353	64	1,948	2,850	.08	.98
6	0	93	159	124	424	0	1,650	2,450	.04	1.02
7	0	108	152	124	325	0	1,521	2,230	0	1.02
8	0	110	164	110	392	0	1,294	2,070	0	1.02
9	238	136	291	116	239	0	1,128	1,910	.17	1.19
10	612	145	455	116	0	0	1,134	1,850	0	1.19

1. Release directed to maintain a flow at Montague of 1,750 cfs.

2. Includes conservation release from Rio Reservoir.

Diversions by New Jersey through the Delaware and Raritan Canal June 4 - 10, 2007, averaged 92.6 mgd. The average diversion for the 30-day period ending June 10, 2007 was 92.7 mgd and the maximum daily diversion was 96 mg on May 27, 31; and June 8, 2007.

1. Release directed to maintain a flow at Montague of 1,750 cfs, June 11 - 14 and 1,800 cfs, June 15 - 17, 2007.

OFFICE OF THE DELAWARE RIVER MASTER, MILFORD, PA.

Web address: <http://water.usgs.gov/orh/nrwww/odrm>

Summary river data for June 11 -17, 2007 (preliminary data-subject to revision)

RESERVOIR OPERATION DATA

Millions of gallons - 24 hour period, local time

Date	Discharge to river			Diversions to New York City water supply			
	Pepacton	Cannonsville	Neversink	Pepacton	Cannonsville	Neversink	Average June 1, 2007 to date
	release begin 1200	release end 2400	release begin 1500	beginning 0800	beginning 0800	beginning 0800	
June 11	94	236	75	450	298	51	680
12	95	261	76	450	297	52	690
13	94	204	80	451	298	52	699
14	95	316	80	366	298	20	698
15	94	468	82	316	297	0	692
16	99	432	94	303	259	0	684
17	100	246	95	304	242	0	676

Pepacton Reservoir (P):	Available storage June 18, 2007 (0800)	133.437 billion gals.	95.2 % (elev. 1,276.29 ft.)
	Spillway crest elevation 1,280.00 ft.	140.190 billion gallons.	
Cannonsville Reservoir (C):	Available storage June 18, 2007 (0800)	86.742 billion gals.	90.6 % (elev. 1,144.06 ft.)
	Spillway crest elevation 1,150.00 ft.	95.706 billion gallons.	
Neversink Reservoir (N):	Available storage June 18, 2007 (0800)	32.510 billion gals.	93.0 % (elev. 1,434.98 ft.)
	Spillway crest elevation 1,440.00 ft.	34.941 billion gallons.	
Combined contents, PCN:	Available storage June 18, 2007 (0800)	252.689 billion gals.	93.3 %
	Combined capacity at spillway level.	270.837 billion gallons.	
Lake Wallenpaupack:	Available storage June 17, 2007 (2400)	26.680 billion gals.	75.3 % (elev. 1,185.3 ft.)
	Spillway crest elevation 1,190.00 ft.	35.451 billion gallons.	

SEGREGATION OF FLOW, DELAWARE RIVER AT MONTAGUE AND
PRECIPITATION IN UPPER DELAWARE RIVER BASIN

Discharge in cubic feet per second, local time as routed to Montague

Date	Releases from N.Y.C. Reservoirs				Power releases		Computed uncon- trolled ²	Total Discharge	Excess Release Credits ³		Precipitation	
	Directed release ¹	Pepacton	Cannons- ville	Never- sink	Wallen- paupack	Rio Reservoir			Daily Cumul.		(inches)	
											Daily	Cumul.
June 11	681	147	415	116	0	0	1,152	1,830	--	--	.02	1.21
12	360	147	364	116	317	0	1,116	2,060	--	--	.06	1.27
13	412	145	365	116	375	0	1,089	2,090	--	--	.17	1.44
14	293	145	404	118	322	0	1,061	2,050	--	--	0	1.44
15	579	147	316	124	302	0	1,021	1,910	152	152	0	1.44
16	766	145	489	124	102	0	890	1,750	0	152	0	1.44
17	998	147	724	127	0	0	962	1,960	210	362	.18	1.62

1. Release directed to maintain a flow at Montague of 1,750 cfs, June 11 - 14 and 1,800 cfs, June 15 - 17, 2007.

2. Includes conservation release from Rio Reservoir.

3. The excess-release quantity for the seasonal period beginning June 15, 2007 is 11,418 cfs-days. Unless banked or release suspended by the Decree Parties, 5,718 cfs-days are to be released to the lower basin. A total of 5,700 cfs-days are to be used for an upper basin habitat protection bank per DRBC Docket No. D-77-20 CP, Revision 7.

Diversion by New Jersey through the Delaware and Raritan Canal June 11 - 17, 2007, averaged 95.7 mgd. The average diversion for the 30-day period ending June 17, 2007 was 93.9 mgd and the maximum daily diversion was 99 mgd on June 17, 2007.

OFFICE OF THE DELAWARE RIVER MASTER, MILFORD, PA.

Web address: <http://water.usgs.gov/orh/nrwww/odrm>

Summary river data for June 18 -24, 2007 (preliminary data-subject to revision)

RESERVOIR OPERATION DATA

Millions of gallons - 24 hour period, local time

Date	Discharge to river			Diversions to New York City water supply			
	Pepacton	Cannonsville	Neversink	Pepacton	Cannonsville	Neversink	Average June 1, 2007 to date
	release begin 1200	release end 2400	release begin 1500	beginning 0800	beginning 0800	beginning 0800	
June 18	100	332	95	432	20	51	666
19	101	399	92	452	0	0	655
20	61	265	79	29	275	181	646
21	68	145	79	0	433	195	645
22	210	132	80	0	435	338	651
23	100	132	84	0	481	349	659
24	95	150	82	0	481	349	666

Pepacton Reservoir (P):	Available storage June 25, 2007 (0800)	136.927 billion gals.	97.7 % (elev. 1,278.22 ft.)
	Spillway crest elevation 1,280.00 ft.	140.190 billion gallons.	
Cannonsville Reservoir (C):	Available storage June 25, 2007 (0800)	83.894 billion gals.	87.7 % (elev. 1,142.09 ft.)
	Spillway crest elevation 1,150.00 ft.	95.706 billion gallons.	
Neversink Reservoir (N):	Available storage June 25, 2007 (0800)	30.836 billion gals.	88.3 % (elev. 1,431.40 ft.)
	Spillway crest elevation 1,440.00 ft.	34.941 billion gallons.	
Combined contents, PCN:	Available storage June 25, 2007 (0800)	251.657 billion gals.	92.9 %
	Combined capacity at spillway level.	270.837 billion gallons.	
Lake Wallenpaupack:	Available storage June 24, 2007 (2400)	26.680 billion gals.	75.3 % (elev. 1,185.3 ft.)
	Spillway crest elevation 1,190.00 ft.	35.451 billion gallons.	

SEGREGATION OF FLOW, DELAWARE RIVER AT MONTAGUE AND
PRECIPITATION IN UPPER DELAWARE RIVER BASIN

Discharge in cubic feet per second, local time as routed to Montague

Date	Releases from N.Y.C. Reservoirs				Power releases		Computed uncon- trolled ²	Total Discharge	Excess Release Credits ³		Precipitation	
	Directed release ¹	Pepacton	Cannons- ville	Never- sink	Wallen- paupack	Rio Reservoir			Daily Cumul.		(inches)	
											Daily	Cumul.
June 18	955	145	668	145	0	0	852	1,810	60	422	0	1.62
19	682	153	381	147	285	0	834	1,800	50	472	0	1.62
20	572	155	514	147	282	0	1,022	2,120	126	598	.63	2.25
21	862	155	617	142	0	0	3,236	4,150	862	1,460	0	2.25
22	688	156	410	122	0	0	2,142	2,830	688	2,148	.29	2.54
23	0	94	224	122	0	0	1,640	2,080	50	2,198	0	2.54
24	422	105	204	124	0	0	1,317	1,750	0	2,198	0	2.54

1. Release directed to maintain a flow at Montague of 1,800 cfs.

2. Includes conservation release from Rio Reservoir.

3. The excess-release quantity for the seasonal period beginning June 15, 2007 is 11,418 cfs-days. Unless banked or release suspended by the Decree Parties, 5,718 cfs-days are to be released to the lower basin. A total of 5,700 cfs-days are to be used for an upper basin habitat protection bank per DRBC Docket No. D-77-20 CP, Revision 7.

Diversion by New Jersey through the Delaware and Raritan Canal June 18 - 24, 2007, averaged 97.1 mgd. The average diversion for the 30-day period ending June 24, 2007 was 94.9 mgd and the maximum daily diversion was 101 mg on June 19, 2007.

OFFICE OF THE DELAWARE RIVER MASTER, MILFORD, PA.

Web address: <http://water.usgs.gov/orh/nrwww/odrm>

Summary river data for June 25 - July 1, 2007 (preliminary data-subject to revision)

RESERVOIR OPERATION DATA

Millions of gallons - 24 hour period, local time

Date	Discharge to river			Diversions to New York City water supply			
	Pepacton	Cannonsville	Neversink	Pepacton	Cannonsville	Neversink	Average June 1, 2007 to date
	release begin 1200	release end 2400	release begin 1500	beginning 0800	beginning 0800	beginning 0800	
June 25	95	348	85	334	350	349	681
26	98	395	94	500	203	100	686
27	100	410	95	501	198	110	690
28	146	410	85	501	198	50	692
29	319	252	85	498	199	101	696
30	383	201	85	499	199	0	696
July 1	400	151	85	498	199	0	696

Pepacton Reservoir (P):	Available storage July 2, 2007 (0800)	133.455 billion gals.	95.2 % (elev. 1,276.30 ft.)
	Spillway crest elevation 1,280.00 ft.	140.190 billion gallons.	
Cannonsville Reservoir (C):	Available storage July 2, 2007 (0800)	80.964 billion gals.	84.6 % (elev. 1,140.00 ft.)
	Spillway crest elevation 1,150.00 ft.	95.706 billion gallons.	
Neversink Reservoir (N):	Available storage July 2, 2007 (0800)	29.719 billion gals.	85.1 % (elev. 1,428.95 ft.)
	Spillway crest elevation 1,440.00 ft.	34.941 billion gallons.	
Combined contents, PCN:	Available storage July 2, 2007 (0800)	244.138 billion gals.	90.1 %
	Combined capacity at spillway level.	270.837 billion gallons.	
Lake Wallenpaupack:	Available storage July 1, 2007 (2400)	25.950 billion gals.	73.2 % (elev. 1,184.9 ft.)
	Spillway crest elevation 1,190.00 ft.	35.451 billion gallons.	

SEGREGATION OF FLOW, DELAWARE RIVER AT MONTAGUE AND
PRECIPITATION IN UPPER DELAWARE RIVER BASIN

Discharge in cubic feet per second, local time as routed to Montague

Date	Releases from N.Y.C. Reservoirs				Power releases		Computed uncon- trolled ²	Total Discharge	Excess Release Credits ³		Precipitation	
	Directed release ¹	Pepacton	Cannons- ville	Never- sink	Wallen- paupack	Rio Reservoir			Daily Cumul.		(inches)	
											Daily	Cumul.
June 25	654	325	204	130	59	0	1,022	1,740	-10	2,188	0	2.54
26	0	155	232	127	673	0	1,023	2,210	50	2,238	0	2.54
27	506	147	538	131	288	0	906	2,010	50	2,288	0	2.54
28	551	147	611	145	213	0	1,084	2,200	98	2,386	.64	3.18
29	906	152	634	147	372	0	1,235	2,540	763	3,149	.28	3.46
30	919	155	634	131	0	0	1,080	2,000	250	3,399	0	3.46
July 1	753	226	390	131	0	0	953	1,700	-50	3,349	.03	.03

1. Release directed to maintain a flow at Montague of 1,800 cfs.

2. Includes conservation release from Rio Reservoir.

3. The excess-release quantity for the seasonal period beginning June 15, 2007 is 11,418 cfs-days. Unless banked or release suspended by the Decree Parties, 5,718 cfs-days are to be released to the lower basin. A total of 5,700 cfs-days are to be used for an upper basin habitat protection bank per DRBC Docket No. D-77-20 CP, Revision 7.

Diversions by New Jersey through the Delaware and Raritan Canal June 25 - July 1, 2007, averaged 94.0 mgd. The average diversion for the 30-day period ending July 1, 2007 was 94.8 mgd and the maximum daily diversion was 101 mg on June 19, 2007.

OFFICE OF THE DELAWARE RIVER MASTER, MILFORD, PA.

Web address: <http://water.usgs.gov/orh/nrwww/odrm>

Summary river data for July 2-8, 2007 (preliminary data-subject to revision)

RESERVOIR OPERATION DATA

Millions of gallons - 24 hour period, local time

Date	Discharge to river			Diversions to New York City water supply			
	Pepacton	Cannonsville	Neversink	Pepacton	Cannonsville	Neversink	Average June 1, 2007 to date
	release begin 1200	release end 2400	release begin 1500	beginning 0800	beginning 0800	beginning 0800	
July 2	176	151	85	500	199	104	699
3	153	135	84	499	199	53	701
4	89	134	73	493	197	54	702
5	180	114	85	375	200	52	700
6	121	122	85	499	200	51	701
7	120	231	85	499	200	0	701
8	120	294	85	499	200	0	701

Pepacton Reservoir (P):	Available storage July 9, 2007 (0800)	130.226 billion gals.	92.9 % (elev. 1,274.49 ft.)
	Spillway crest elevation 1,280.00 ft.	140.190 billion gallons.	
Cannonsville Reservoir (C):	Available storage July 9, 2007 (0800)	78.940 billion gals.	82.5 % (elev. 1,138.60 ft.)
	Spillway crest elevation 1,150.00 ft.	95.706 billion gallons.	
Neversink Reservoir (N):	Available storage July 9, 2007 (0800)	29.199 billion gals.	83.6 % (elev. 1,427.79 ft.)
	Spillway crest elevation 1,440.00 ft.	34.941 billion gallons.	
Combined contents, PCN:	Available storage July 9, 2007 (0800)	238.365 billion gals.	88.0 %
	Combined capacity at spillway level.	270.837 billion gallons.	
Lake Wallenpaupack:	Available storage July 8, 2007 (2400)	25.037 billion gals.	70.6 % (elev. 1,184.4 ft.)
	Spillway crest elevation 1,190.00 ft.	35.451 billion gallons.	

SEGREGATION OF FLOW, DELAWARE RIVER AT MONTAGUE AND
PRECIPITATION IN UPPER DELAWARE RIVER BASIN

Discharge in cubic feet per second, local time as routed to Montague

Date	Releases from N.Y.C. Reservoirs				Power releases		Computed uncon- trolled ²	Total Discharge	Excess Release Credits ³		Precipitation	
	Directed release ¹	Pepacton	Cannons- ville	Never- sink	Wallen- paupack	Rio Reservoir			Daily Cumul.		(inches)	
											Daily	Cumul.
July 2	936	500	311	131	0	0	778	1,720	-30	3,319	0	.03
3	945	582	234	131	6	0	727	1,680	-70	3,249	0	.03
4	995	630	234	131	0	0	665	1,660	-90	3,159	0	.03
5	613	272	209	130	298	0	881	1,790	40	3,199	.79	.82
6	572	237	207	113	429	0	1,524	2,510	557	3,756	.68	1.50
7	0	138	176	131	583	0	1,792	2,820	0	3,756	.05	1.55
8	597	278	189	131	373	0	1,249	2,220	470	4,226	0	1.55

1. Release directed to maintain a flow at Montague of 1,800 cfs.

2. Includes conservation release from Rio Reservoir.

3. The excess-release quantity for the seasonal period beginning June 15, 2007 is 11,418 cfs-days. Unless banked or release suspended by the Decree Parties, 5,718 cfs-days are to be released to the lower basin. A total of 5,700 cfs-days are to be used for an upper basin habitat protection bank per DRBC Docket No. D-77-20 CP, Revision 7.

Divisions by New Jersey through the Delaware and Raritan Canal July 2-8, 2007, averaged 88.1 mgd. The average diversion for the 30-day period ending July 8, 2007 was 93.8 mgd and the maximum daily diversion was 101 mg on June 19, 2007.

OFFICE OF THE DELAWARE RIVER MASTER, MILFORD, PA.

Web address: <http://water.usgs.gov/orh/nrwww/odrm>

Summary river data for July 9 - 15, 2007 (preliminary data-subject to revision)

RESERVOIR OPERATION DATA

Millions of gallons - 24 hour period, local time

Date	Discharge to river			Diversions to New York City water supply			
	Pepacton	Cannonsville	Neversink	Pepacton	Cannonsville	Neversink	Average June 1, 2007 to date
	release begin 1200	release end 2400	release begin 1500	beginning 0800	beginning 0800	beginning 0800	
July 9	119	320	100	501	200	52	703
10	120	376	98	501	200	53	704
11	106	351	85	501	199	51	705
12	257	312	80	498	285	0	707
13	269	226	90	500	298	0	709
14	129	256	90	500	298	0	711
15	100	277	89	500	298	0	713

Pepacton Reservoir (P):	Available storage July 16, 2007 (0800)	126.464 billion gals.	90.2 % (elev. 1,272.35 ft.)
	Spillway crest elevation 1,280.00 ft.	140.190 billion gallons.	
Cannonsville Reservoir (C):	Available storage July 16, 2007 (0800)	75.721 billion gals.	79.1 % (elev. 1,136.27 ft.)
	Spillway crest elevation 1,150.00 ft.	95.706 billion gallons.	
Neversink Reservoir (N):	Available storage July 16, 2007 (0800)	28.526 billion gals.	81.6 % (elev. 1,426.27 ft.)
	Spillway crest elevation 1,440.00 ft.	34.941 billion gallons.	
Combined contents, PCN:	Available storage July 16, 2007 (0800)	230.711 billion gals.	85.2 %
	Combined capacity at spillway level.	270.837 billion gallons.	
Lake Wallenpaupack:	Available storage July 15, 2007 (2400)	23.942 billion gals.	67.5 % (elev. 1,183.8 ft.)
	Spillway crest elevation 1,190.00 ft.	35.451 billion gallons.	

SEGREGATION OF FLOW, DELAWARE RIVER AT MONTAGUE AND
PRECIPITATION IN UPPER DELAWARE RIVER BASIN

Discharge in cubic feet per second, local time as routed to Montague

Date	Releases from N.Y.C. Reservoirs				Power releases		Computed uncon- trolled ²	Total Discharge	Excess Release Credits ³		Precipitation	
	Directed release ¹	Pepacton	Cannons- ville	Never- sink	Wallen- paupack	Rio Reservoir			Daily Cumul.		(inches)	
											Daily	Cumul.
July 9	603	187	357	131	355	89	921	2,040	218	4,444	.08	1.63
10	325	186	455	131	451	152	835	2,210	50	4,494	0	1.63
11	421	186	495	155	481	113	770	2,200	50	4,544	.05	1.68
12	346	184	582	152	434	0	918	2,270	50	4,594	.28	1.96
13	0	186	543	131	410	0	820	2,090	50	4,644	0	1.96
14	166	164	483	124	482	0	757	2,010	50	4,694	.01	1.97
15	863	398	350	139	33	0	690	1,610	-140	4,554	0	1.97

1. Release directed to maintain a flow at Montague of 1,800 cfs.

2. Includes conservation release from Rio Reservoir.

3. The excess-release quantity for the seasonal period beginning June 15, 2007 is 11,418 cfs-days. Unless banked or release suspended by the Decree Parties, 5,718 cfs-days are to be released to the lower basin. A total of 5,700 cfs-days are to be used for an upper basin habitat protection bank per DRBC Docket No. D-77-20 CP, Revision 7.

Diversion by New Jersey through the Delaware and Raritan Canal July 9 - 15, 2007, averaged 97.7 mgd. The average diversion for the 30-day period ending July 15, 2007 was 94.5 mgd and the maximum daily diversion was 103 mg on July 13, 14, 2007.

OFFICE OF THE DELAWARE RIVER MASTER, MILFORD, PA.

Web address: <http://water.usgs.gov/orh/nrwww/odrm>

Summary river data for July 16 - 22, 2007 (preliminary data-subject to revision)

RESERVOIR OPERATION DATA

Millions of gallons - 24 hour period, local time

Date	Discharge to river			Diversions to New York City water supply			
	Pepacton	Cannonsville	Neversink	Pepacton	Cannonsville	Neversink	Average June 1, 2007 to date
	release begin 1200	release end 2400	release begin 1500	beginning 0800	beginning 0800	beginning 0800	
July 16	101	270	84	500	298	0	715
17	101	261	80	500	298	0	717
18	101	249	75	499	298	0	718
19	101	183	75	499	298	0	720
20	228	150	80	500	298	0	721
21	103	340	80	500	298	0	723
22	100	191	80	500	298	0	724

Pepacton Reservoir (P):	Available storage July 23, 2007 (0800)	122.929 billion gals.	87.7 % (elev. 1,270.31 ft.)
	Spillway crest elevation 1,280.00 ft.	140.190 billion gallons.	
Cannonsville Reservoir (C):	Available storage July 23, 2007 (0800)	72.907 billion gals.	76.2 % (elev. 1,134.20 ft.)
	Spillway crest elevation 1,150.00 ft.	95.706 billion gallons.	
Neversink Reservoir (N):	Available storage July 23, 2007 (0800)	28.105 billion gals.	80.4 % (elev. 1,425.31 ft.)
	Spillway crest elevation 1,440.00 ft.	34.941 billion gallons.	
Combined contents, PCN:	Available storage July 23, 2007 (0800)	223.941 billion gals.	82.7 %
	Combined capacity at spillway level.	270.837 billion gallons.	
Lake Wallenpaupack:	Available storage July 22, 2007 (2400)	22.665 billion gals.	63.9 % (elev. 1,183.1 ft.)
	Spillway crest elevation 1,190.00 ft.	35.451 billion gallons.	

SEGREGATION OF FLOW, DELAWARE RIVER AT MONTAGUE AND
PRECIPITATION IN UPPER DELAWARE RIVER BASIN

Discharge in cubic feet per second, local time as routed to Montague

Date	Releases from N.Y.C. Reservoirs				Power releases		Computed uncon- trolled ²	Total Discharge	Excess Release Credits ³		Precipitation	
	Directed release ¹	Pepacton	Cannons- ville	Never- sink	Wallen- paupack	Rio Reservoir			Daily Cumul.		(inches)	
											Daily	Cumul.
July 16	926	416	396	139	4	0	705	1,660	-90	4,464	.23	2.20
17	530	200	429	138	410	0	653	1,830	50	4,514	0	2.20
18	484	155	418	130	576	0	681	1,960	50	4,564	.40	2.60
19	576	156	404	124	401	0	735	1,820	50	4,614	.01	2.61
20	393	156	385	116	388	0	815	1,860	50	4,664	.43	3.04
21	0	156	283	116	532	0	843	1,930	50	4,714	0	3.04
22	0	156	232	124	0	0	748	1,260	-490	4,224	0	3.04

1. Release directed to maintain a flow at Montague of 1,800 cfs.

2. Includes conservation release from Rio Reservoir.

3. The excess-release quantity for the seasonal period beginning June 15, 2007 is 11,418 cfs-days. Unless banked or release suspended by the Decree Parties, 5,718 cfs-days are to be released to the lower basin. A total of 5,700 cfs-days are to be used for an upper basin habitat protection bank per DRBC Docket No. D-77-20 CP, Revision 7.

Diversions by New Jersey through the Delaware and Raritan Canal July 16 - 22, 2007, averaged 98.6 mgd. The average diversion for the 30-day period ending July 22, 2007 was 94.8 mgd and the maximum daily diversion was 104 mg on July 19, 2007.

OFFICE OF THE DELAWARE RIVER MASTER, MILFORD, PA.

Web address: <http://water.usgs.gov/orh/nrwww/odrm>

Summary river data for July 23 - 29, 2007 (preliminary data-subject to revision)

RESERVOIR OPERATION DATA

Millions of gallons - 24 hour period, local time

Date	Discharge to river			Diversions to New York City water supply			
	Pepacton	Cannonsville	Neversink	Pepacton	Cannonsville	Neversink	Average June 1, 2007 to date
	release begin 1200	release end 2400	release begin 1500	beginning 0800	beginning 0800	beginning 0800	
July 23	100	139	80	501	299	0	726
24	100	139	80	501	299	0	727
25	100	157	90	501	299	0	728
26	100	219	90	501	299	0	730
27	99	258	88	501	199	0	729
28	96	242	74	501	199	0	729
29	106	246	64	501	199	0	728

Pepacton Reservoir (P):	Available storage July 30, 2007 (0800)	120.038 billion gals.	85.6 % (elev. 1,268.62 ft.)
	Spillway crest elevation 1,280.00 ft.	140.190 billion gallons.	
Cannonsville Reservoir (C):	Available storage July 30, 2007 (0800)	70.801 billion gals.	74.0 % (elev. 1,132.61 ft.)
	Spillway crest elevation 1,150.00 ft.	95.706 billion gallons.	
Neversink Reservoir (N):	Available storage July 30, 2007 (0800)	28.014 billion gals.	80.2 % (elev. 1,425.10 ft.)
	Spillway crest elevation 1,440.00 ft.	34.941 billion gallons.	
Combined contents, PCN:	Available storage July 30, 2007 (0800)	218.853 billion gals.	80.8 %
	Combined capacity at spillway level.	270.837 billion gallons.	
Lake Wallenpaupack:	Available storage July 29, 2007 (2400)	22.303 billion gals.	62.9 % (elev. 1,182.9 ft.)
	Spillway crest elevation 1,190.00 ft.	35.451 billion gallons.	

SEGREGATION OF FLOW, DELAWARE RIVER AT MONTAGUE AND
PRECIPITATION IN UPPER DELAWARE RIVER BASIN

Discharge in cubic feet per second, local time as routed to Montague

Date	Releases from N.Y.C. Reservoirs				Power releases		Computed uncon- trolled ²	Total Discharge	Excess Release Credits ³		Precipitation	
	Directed release ¹	Pepacton	Cannons- ville	Never- sink	Wallen- paupack	Rio Reservoir			Daily Cumul.		(inches)	
											Daily	Cumul.
July 23	1,002	353	526	124	0	0	697	1,700	-50	4,174	0	3.04
24	575	159	295	124	383	0	2,089	3,050	578	4,752	1.71	4.75
25	0	155	215	124	432	0	2,194	3,120	0	4,752	0	4.75
26	0	155	215	124	577	0	1,649	2,720	0	4,752	0	4.75
27	0	155	243	139	653	0	1,140	2,330	7	4,759	0	4.75
28	0	155	339	139	542	0	2,215	3,390	0	4,759	.89	5.64
29	225	155	399	136	1,211	0	2,489	4,390	225	4,984	0	5.64

1. Release directed to maintain a flow at Montague of 1,800 cfs.

2. Includes conservation release from Rio Reservoir.

3. The excess-release quantity for the seasonal period beginning June 15, 2007 is 11,418 cfs-days. Unless banked or release suspended by the Decree Parties, 5,718 cfs-days are to be released to the lower basin. A total of 5,700 cfs-days are to be used for an upper basin habitat protection bank per DRBC Docket No. D-77-20 CP, Revision 7.

Diversions by New Jersey through the Delaware and Raritan Canal July 23 - 29, 2007, averaged 99.4 mgd. The average diversion for the 30-day period ending July 29, 2007 was 96.4 mgd and the maximum daily diversion was 105 mg on July 14, 2007.

OFFICE OF THE DELAWARE RIVER MASTER, MILFORD, PA.

Web address: <http://water.usgs.gov/orh/nrwww/odrm>

Summary river data for July 30 - August 5, 2007 (preliminary data-subject to revision)

RESERVOIR OPERATION DATA

Millions of gallons - 24 hour period, local time

Date	Discharge to river			Diversions to New York City water supply			
	Pepacton	Cannonsville	Neversink	Pepacton	Cannonsville	Neversink	Average June 1, 2007 to date
	release begin 1200	release end 2400	release begin 1500	beginning 0800	beginning 0800	beginning 0800	
July 30	121	287	60	501	199	0	728
31	108	299	71	501	199	42	728
Aug. 1	96	300	83	501	199	0	728
2	110	298	94	443	197	0	726
3	125	401	100	500	199	0	726
4	100	453	110	500	199	0	725
5	100	307	100	500	199	0	725

Pepacton Reservoir (P):	Available storage Aug. 6, 2007 (0800)	116.545 billion gals.	83.1 % (elev. 1,266.55 ft.)
	Spillway crest elevation 1,280.00 ft.	140.190 billion gallons.	
Cannonsville Reservoir (C):	Available storage Aug. 6, 2007 (0800)	67.635 billion gals.	70.7 % (elev. 1,130.22 ft.)
	Spillway crest elevation 1,150.00 ft.	95.706 billion gallons.	
Neversink Reservoir (N):	Available storage Aug. 6, 2007 (0800)	27.546 billion gals.	78.8 % (elev. 1,424.02 ft.)
	Spillway crest elevation 1,440.00 ft.	34.941 billion gallons.	
Combined contents, PCN:	Available storage Aug. 6, 2007 (0800)	211.726 billion gals.	78.2 %
	Combined capacity at spillway level.	270.837 billion gallons.	
Lake Wallenpaupack:	Available storage Aug. 5, 2007 (2400)	20.869 billion gals.	58.9 % (elev. 1,182.1 ft.)
	Spillway crest elevation 1,190.00 ft.	35.451 billion gallons.	

SEGREGATION OF FLOW, DELAWARE RIVER AT MONTAGUE AND
PRECIPITATION IN UPPER DELAWARE RIVER BASIN

Discharge in cubic feet per second, local time as routed to Montague

Date	Releases from N.Y.C. Reservoirs				Power releases		Computed uncon- trolled ²	Total Discharge	Excess Release Credits ³		Precipitation	
	Directed release ¹	Pepacton	Cannons- ville	Never- sink	Wallen- paupack	Rio Reservoir			Daily Cumul.		(inches)	
											Daily	Cumul.
July 30	0	153	374	114	1,156	0	2,003	3,800	0	4,984	.12	5.76
31	0	149	381	99	987	0	1,574	3,190	0	4,984	0	5.76
Aug. 1	0	164	444	93	616	0	1,513	2,830	0	4,984	0	0
2	0	187	463	110	318	0	1,162	2,240	50	5,034	0	0
3	346	167	464	128	276	0	1,015	2,050	50	5,084	0	0
4	308	149	461	145	380	0	1,245	2,380	50	5,134	.36	.36
5	943	170	620	155	23	0	1,112	2,080	330	5,464	0	.36

1. Release directed to maintain a flow at Montague of 1,800 cfs.

2. Includes conservation release from Rio Reservoir.

3. The excess-release quantity for the seasonal period beginning June 15, 2007 is 11,418 cfs-days. Unless banked or release suspended by the Decree Parties, 5,718 cfs-days are to be released to the lower basin. A total of 5,700 cfs-days are to be used for an upper basin habitat protection bank per DRBC Docket No. D-77-20 CP, Revision 7.

Diversion by New Jersey through the Delaware and Raritan Canal July 30 - August 5, 2007, averaged 100.3 mgd. The average diversion for the 30-day period ending August 5, 2007 was 98.6 mgd and the maximum daily diversion was 105 mgd on July 14, 2007.

OFFICE OF THE DELAWARE RIVER MASTER, MILFORD, PA.

Web address: <http://water.usgs.gov/orh/nrwww/odrm>

Summary river data for August 6 - 12, 2007 (preliminary data-subject to revision)

RESERVOIR OPERATION DATA

Millions of gallons - 24 hour period, local time

Date	Discharge to river			Diversions to New York City water supply			
	Pepacton	Cannonsville	Neversink	Pepacton	Cannonsville	Neversink	Average June 1, 2007 to date
	release begin 1200	release end 2400	release begin 1500	beginning 0800	beginning 0800	beginning 0800	
Aug. 6	100	286	110	499	199	0	725
7	99	295	94	501	293	0	726
8	112	245	60	501	298	0	727
9	114	197	59	500	298	0	728
10	81	179	45	501	298	0	729
11	85	161	62	501	298	0	730
12	98	212	80	500	298	0	731

Pepacton Reservoir (P):	Available storage Aug. 13, 2007 (0800)	114.031 billion gals.	81.3 % (elev. 1,265.04 ft.)
	Spillway crest elevation 1,280.00 ft.	140.190 billion gallons.	
Cannonsville Reservoir (C):	Available storage Aug. 13, 2007 (0800)	65.472 billion gals.	68.4 % (elev. 1,128.53 ft.)
	Spillway crest elevation 1,150.00 ft.	95.706 billion gallons.	
Neversink Reservoir (N):	Available storage Aug. 13, 2007 (0800)	27.584 billion gals.	78.9 % (elev. 1,424.11 ft.)
	Spillway crest elevation 1,440.00 ft.	34.941 billion gallons.	
Combined contents, PCN:	Available storage Aug. 13, 2007 (0800)	207.087 billion gals.	76.5 %
	Combined capacity at spillway level.	270.837 billion gallons.	
Lake Wallenpaupack:	Available storage Aug. 12, 2007 (2400)	20.511 billion gals.	57.9 % (elev. 1,181.9 ft.)
	Spillway crest elevation 1,190.00 ft.	35.451 billion gallons.	

SEGREGATION OF FLOW, DELAWARE RIVER AT MONTAGUE AND
PRECIPITATION IN UPPER DELAWARE RIVER BASIN

Discharge in cubic feet per second, local time as routed to Montague

Date	Releases from N.Y.C. Reservoirs				Power releases		Computed uncon- trolled ²	Total Discharge	Excess Release Credits ³		Precipitation	
	Directed release ¹	Pepacton	Cannons- ville	Never- sink	Wallen- paupack	Rio Reservoir			Daily Cumul.		(inches)	
											Daily	Cumul.
Aug. 6	1,059	193	701	170	0	0	896	1,960	123	5,718	.05	.41
7	731	155	475	155	323	0	882	1,990	*expended*		0	.41
8	666	155	442	170	327	0	1,176	2,270	--	--	.87	1.28
9	706	155	456	145	351	0	1,773	2,880	--	--	.01	1.29
10	354	153	379	93	293	0	2,502	3,420	--	--	1.05	2.34
11	68	173	305	91	435	0	3,406	4,410	--	--	.28	2.62
12	187	176	277	70	0	0	2,957	3,480	--	--	0	2.62

1. Release directed to maintain a flow at Montague of 1,800 cfs on August 6 - 9, 2007 and 1,750 cfs on August 10 - 12, 2007.

2. Includes conservation release from Rio Reservoir.

3. The excess-release quantity for the seasonal period beginning June 15, 2007 is 11,418 cfs-days. Unless banked or release suspended by the Decree Parties, 5,718 cfs-days are to be released to the lower basin. A total of 5,700 cfs-days are to be used for an upper basin habitat protection bank per DRBC Docket No. D-77-20 CP, Revision 7.

Diversion by New Jersey through the Delaware and Raritan Canal August 6 - 12, 2007, averaged 98.4 mgd. The average diversion for the 30-day period ending August 12, 2007 was 99.5 mgd and the maximum daily diversion was 105 mg on July 14, 2007.

OFFICE OF THE DELAWARE RIVER MASTER, MILFORD, PA.

Web address: <http://water.usgs.gov/orh/nrwww/odrm>

Summary river data for August 13 - 19, 2007 (preliminary data-subject to revision)

RESERVOIR OPERATION DATA

Millions of gallons - 24 hour period, local time

Date	Discharge to river			Diversions to New York City water supply			
	Pepacton	Cannonsville	Neversink	Pepacton	Cannonsville	Neversink	Average June 1, 2007 to date
	release begin 1200	release end 2400	release begin 1500	beginning 0800	beginning 0800	beginning 0800	
Aug. 13	100	238	80	281	298	0	729
14	84	239	75	500	298	0	729
15	84	239	72	500	298	0	730
16	94	221	70	454	210	0	729
17	94	424	75	444	196	0	728
18	95	347	75	448	198	0	727
19	94	241	75	448	198	0	726

Pepacton Reservoir (P):	Available storage Aug. 20, 2007 (0800)	111.301 billion gals.	79.4 % (elev. 1,263.38 ft.)
	Spillway crest elevation 1,280.00 ft.	140.190 billion gallons.	
Cannonsville Reservoir (C):	Available storage Aug. 20, 2007 (0800)	62.670 billion gals.	65.5 % (elev. 1,126.33 ft.)
	Spillway crest elevation 1,150.00 ft.	95.706 billion gallons.	
Neversink Reservoir (N):	Available storage Aug. 20, 2007 (0800)	27.249 billion gals.	78.0 % (elev. 1,423.33 ft.)
	Spillway crest elevation 1,440.00 ft.	34.941 billion gallons.	
Combined contents, PCN:	Available storage Aug. 20, 2007 (0800)	201.220 billion gals.	74.3 %
	Combined capacity at spillway level.	270.837 billion gallons.	
Lake Wallenpaupack:	Available storage Aug. 19, 2007 (2400)	20.152 billion gals.	56.8 % (elev. 1,181.7 ft.)
	Spillway crest elevation 1,190.00 ft.	35.451 billion gallons.	

SEGREGATION OF FLOW, DELAWARE RIVER AT MONTAGUE AND
PRECIPITATION IN UPPER DELAWARE RIVER BASIN

Discharge in cubic feet per second, local time as routed to Montague

Date	Releases from N.Y.C. Reservoirs				Power releases		Computed uncon- trolled ²	Total Discharge	Precipitation	
	Directed release ¹	Pepacton	Cannons- ville	Never- sink	Wallen- paupack	Rio Reservoir			(inches)	
							Daily	Cumul.		
Aug. 13	438	125	249	96	0	0	2,230	2,700	0	2.62
14	0	131	328	124	484	0	1,733	2,800	0	2.62
15	0	152	368	124	434	0	1,422	2,500	0	2.62
16	83	155	370	116	555	18	1,276	2,490	0	2.62
17	306	130	370	111	633	195	1,091	2,530	.16	2.78
18	491	130	342	108	325	0	1,115	2,020	.06	2.84
19	921	145	656	116	7	0	1,116	2,040	0	2.84

1. Release directed to maintain a flow at Montague of 1,750 cfs.

2. Includes conservation release from Rio Reservoir.

Diversions by New Jersey through the Delaware and Raritan Canal August 13 - 19, 2007, averaged 94.9 mgd. The average diversion for the 30-day period ending August 19, 2007 was 98.1 mgd and the maximum daily diversion was 103 mgd on August 2, 2007.

OFFICE OF THE DELAWARE RIVER MASTER, MILFORD, PA.

Web address: <http://water.usgs.gov/orh/nrwww/odrm>

Summary river data for August 20 - 26, 2007 (preliminary data-subject to revision)

RESERVOIR OPERATION DATA

Millions of gallons - 24 hour period, local time

Date	Discharge to river			Diversions to New York City water supply			
	Pepacton	Cannonsville	Neversink	Pepacton	Cannonsville	Neversink	Average June 1, 2007 to date
	release begin 1200	release end 2400	release begin 1500	beginning 0800	beginning 0800	beginning 0800	
Aug. 20	90	291	75	444	198	0	725
21	90	215	70	448	197	0	724
22	90	136	70	451	198	0	723
23	110	129	70	451	198	0	722
24	101	281	81	411	198	0	721
25	108	300	90	404	198	0	720
26	100	293	77	404	199	0	718

Pepacton Reservoir (P):	Available storage Aug. 27, 2007 (0800)	108.669 billion gals.	77.5 % (elev. 1,261.76 ft.)
	Spillway crest elevation 1,280.00 ft.	140.190 billion gallons.	
Cannonsville Reservoir (C):	Available storage Aug. 27, 2007 (0800)	60.744 billion gals.	63.5 % (elev. 1,124.81 ft.)
	Spillway crest elevation 1,150.00 ft.	95.706 billion gallons.	
Neversink Reservoir (N):	Available storage Aug. 27, 2007 (0800)	26.979 billion gals.	77.2 % (elev. 1,422.70 ft.)
	Spillway crest elevation 1,440.00 ft.	34.941 billion gallons.	
Combined contents, PCN:	Available storage Aug. 27, 2007 (0800)	196.392 billion gals.	72.5 %
	Combined capacity at spillway level.	270.837 billion gallons.	
Lake Wallenpaupack:	Available storage Aug. 26, 2007 (2400)	19.615 billion gals.	55.3 % (elev. 1,181.4 ft.)
	Spillway crest elevation 1,190.00 ft.	35.451 billion gallons.	

SEGREGATION OF FLOW, DELAWARE RIVER AT MONTAGUE AND
PRECIPITATION IN UPPER DELAWARE RIVER BASIN

Discharge in cubic feet per second, local time as routed to Montague

Date	Releases from N.Y.C. Reservoirs				Power releases		Computed uncon- trolled ²	Total Discharge	Precipitation	
	Directed release ¹	Pepacton	Cannons- ville	Never- sink	Wallen- paupack	Rio Reservoir			(inches)	
							Daily	Cumul.		
Aug. 20	799	145	537	116	0	0	1,032	1,830	0	2.84
21	632	147	373	116	268	0	1,236	2,140	.38	3.22
22	713	145	450	116	608	0	1,621	2,940	.57	3.79
23	578	139	333	108	476	0	1,604	2,660	.01	3.80
24	269	139	210	108	560	0	1,483	2,500	.02	3.82
25	166	139	200	108	619	0	1,304	2,370	.03	3.85
26	726	170	435	125	393	0	1,087	2,210	.04	3.89

1. Release directed to maintain a flow at Montague of 1,750 cfs.

2. Includes conservation release from Rio Reservoir.

Diversions by New Jersey through the Delaware and Raritan Canal August 20 - 26, 2007, averaged 97.9 mgd. The average diversion for the 30-day period ending August 26, 2007 was 98.0 mgd and the maximum daily diversion was 105 mgd on August 24, 2007.

OFFICE OF THE DELAWARE RIVER MASTER, MILFORD, PA.

Web address: <http://water.usgs.gov/orh/nrwww/odrm>

Summary river data for August 27 - September 2, 2007 (preliminary data-subject to revision)

RESERVOIR OPERATION DATA

Millions of gallons - 24 hour period, local time

Date	Discharge to river			Diversions to New York City water supply			
	Pepacton	Cannonsville	Neversink	Pepacton	Cannonsville	Neversink	Average June 1, 2007 to date
	release begin 1200	release end 2400	release begin 1500	beginning 0800	beginning 0800	beginning 0800	
Aug. 27	95	265	75	401	199	0	717
28	95	270	75	400	273	0	717
29	95	272	75	402	299	0	716
30	100	330	75	402	298	0	716
31	100	605	80	501	266	0	717
Sept. 1	100	572	80	315	152	0	714
2	100	567	80	491	264	0	715

Pepacton Reservoir (P):	Available storage Sept. 3, 2007 (0800)	105.589 billion gals.	75.3 % (elev. 1,259.84 ft.)
	Spillway crest elevation 1,280.00 ft.	140.190 billion gallons.	
Cannonsville Reservoir (C):	Available storage Sept. 3, 2007 (0800)	56.202 billion gals.	58.7 % (elev. 1,121.09 ft.)
	Spillway crest elevation 1,150.00 ft.	95.706 billion gallons.	
Neversink Reservoir (N):	Available storage Sept. 3, 2007 (0800)	26.570 billion gals.	76.0 % (elev. 1,421.74 ft.)
	Spillway crest elevation 1,440.00 ft.	34.941 billion gallons.	
Combined contents, PCN:	Available storage Sept. 3, 2007 (0800)	188.361 billion gals.	69.5 %
	Combined capacity at spillway level.	270.837 billion gallons.	
Lake Wallenpaupack:	Available storage Sept. 2, 2007 (2400)	19.077 billion gals.	53.8 % (elev. 1,181.1 ft.)
	Spillway crest elevation 1,190.00 ft.	35.451 billion gallons.	

SEGREGATION OF FLOW, DELAWARE RIVER AT MONTAGUE AND
PRECIPITATION IN UPPER DELAWARE RIVER BASIN

Discharge in cubic feet per second, local time as routed to Montague

Date	Releases from N.Y.C. Reservoirs				Power releases		Computed uncon- trolled ²	Total Discharge	Precipitation	
	Directed release ¹	Pepacton	Cannons- ville	Never- sink	Wallen- paupack	Rio Reservoir			(inches)	
							Daily	Cumul.		
Aug. 27	447	156	464	139	410	0	1,071	2,240	0	3.89
28	381	167	453	119	417	0	974	2,130	0	3.89
29	458	155	410	116	295	0	914	1,890	0	3.89
30	604	147	418	116	336	0	843	1,860	0	3.89
31	678	147	421	116	303	0	793	1,780	0	3.89
Sept. 1	772	147	511	116	426	0	730	1,930	0	0
2	1,220	155	936	124	0	0	635	1,850	0	0

1. Release directed to maintain a flow at Montague of 1,750 cfs.

2. Includes conservation release from Rio Reservoir.

Diversions by New Jersey through the Delaware and Raritan Canal August 27 - September 2, 2007, averaged 99.4 mgd. The average diversion for the 30-day period ending September 2, 2007 was 97.7 mgd and the maximum daily diversion was 105 mgd on August 24, 2007.

OFFICE OF THE DELAWARE RIVER MASTER, MILFORD, PA.

Web address: <http://water.usgs.gov/orh/nrwww/odrm>

Summary river data for September 3 - 9, 2007 (preliminary data-subject to revision)

RESERVOIR OPERATION DATA

Millions of gallons - 24 hour period, local time

Date	Discharge to river			Diversions to New York City water supply			
	Pepacton	Cannonsville	Neversink	Pepacton	Cannonsville	Neversink	Average June 1, 2007 to date
	release begin 1200	release end 2400	release begin 1500	beginning 0800	beginning 0800	beginning 0800	
Sept. 3	100	339	84	491	263	0	715
4	100	347	85	501	99	165	715
5	110	380	85	500	0	266	716
6	110	390	85	502	0	266	717
7	115	427	85	502	0	350	718
8	115	487	85	500	0	350	719
9	115	242	85	499	0	317	720

Pepacton Reservoir (P):	Available storage Sept. 10, 2007 (0800)	102.179 billion gals.	72.9 % (elev. 1,257.68 ft.)
	Spillway crest elevation 1,280.00 ft.	140.190 billion gallons.	
Cannonsville Reservoir (C):	Available storage Sept. 10, 2007 (0800)	53.809 billion gals.	56.2 % (elev. 1,119.09 ft.)
	Spillway crest elevation 1,150.00 ft.	95.706 billion gallons.	
Neversink Reservoir (N):	Available storage Sept. 10, 2007 (0800)	24.486 billion gals.	70.1 % (elev. 1,416.73 ft.)
	Spillway crest elevation 1,440.00 ft.	34.941 billion gallons.	
Combined contents, PCN:	Available storage Sept. 10, 2007 (0800)	180.474 billion gals.	66.6 %
	Combined capacity at spillway level.	270.837 billion gallons.	
Lake Wallenpaupack:	Available storage Sept. 9, 2007 (2400)	17.666 billion gals.	49.8 % (elev. 1,180.3 ft.)
	Spillway crest elevation 1,190.00 ft.	35.451 billion gallons.	

SEGREGATION OF FLOW, DELAWARE RIVER AT MONTAGUE AND
PRECIPITATION IN UPPER DELAWARE RIVER BASIN

Discharge in cubic feet per second, local time as routed to Montague

Date	Releases from N.Y.C. Reservoirs				Power releases		Computed uncon- trolled ²	Total Discharge	Precipitation	
	Directed release ¹	Pepacton	Cannons- ville	Never- sink	Wallen- paupack	Rio Reservoir			(inches)	
									Daily	Cumul.
Sept. 3	1,168	155	885	124	0	0	646	1,810	0	0
4	1,157	155	877	124	0	0	624	1,780	0	0
5	814	155	524	130	404	0	687	1,900	0	0
6	821	155	537	131	350	0	607	1,780	0	0
7	876	155	588	131	417	35	564	1,890	0	0
8	905	170	603	131	393	71	582	1,950	0	0
9	965	170	661	131	423	0	745	2,130	.44	.44

1. Release directed to maintain a flow at Montague of 1,750 cfs.

2. Includes conservation release from Rio Reservoir.

Divisions by New Jersey through the Delaware and Raritan Canal September 3 - 9, 2007, averaged 96.9 mgd. The average diversion for the 30-day period ending September 9, 2007 was 97.2 mgd and the maximum daily diversion was 105 mg on August 24, 2007.

OFFICE OF THE DELAWARE RIVER MASTER, MILFORD, PA.

Web address: <http://water.usgs.gov/orh/nrwww/odrm>

Summary river data for September 10 - 16, 2007 (preliminary data-subject to revision)

RESERVOIR OPERATION DATA

Millions of gallons - 24 hour period, local time

Date	Discharge to river			Diversions to New York City water supply			
	Pepacton	Cannonsville	Neversink	Pepacton	Cannonsville	Neversink	Average June 1, 2007 to date
	release begin 1200	release end 2400	release begin 1500	beginning 0800	beginning 0800	beginning 0800	
Sept. 10	115	250	84	498	0	258	721
11	115	257	85	501	188	56	721
12	90	228	85	500	265	0	721
13	80	132	80	497	262	0	722
14	80	412	80	502	200	0	721
15	80	493	80	502	200	0	721
16	80	223	80	502	200	0	721

Pepacton Reservoir (P):	Available storage Sept. 17, 2007 (0800)	101.164 billion gals.	72.2 % (elev. 1,257.03 ft.)
	Spillway crest elevation 1,280.00 ft.	140.190 billion gallons.	
Cannonsville Reservoir (C):	Available storage Sept. 17, 2007 (0800)	53.891 billion gals.	56.3 % (elev. 1,119.16 ft.)
	Spillway crest elevation 1,150.00 ft.	95.706 billion gallons.	
Neversink Reservoir (N):	Available storage Sept. 17, 2007 (0800)	24.031 billion gals.	68.8 % (elev. 1,415.61 ft.)
	Spillway crest elevation 1,440.00 ft.	34.941 billion gallons.	
Combined contents, PCN:	Available storage Sept. 17, 2007 (0800)	179.086 billion gals.	66.1 %
	Combined capacity at spillway level.	270.837 billion gallons.	
Lake Wallenpaupack:	Available storage Sept. 16, 2007 (2400)	17.490 billion gals.	49.3 % (elev. 1,180.2 ft.)
	Spillway crest elevation 1,190.00 ft.	35.451 billion gallons.	

SEGREGATION OF FLOW, DELAWARE RIVER AT MONTAGUE AND
PRECIPITATION IN UPPER DELAWARE RIVER BASIN

Discharge in cubic feet per second, local time as routed to Montague

Date	Releases from N.Y.C. Reservoirs				Power releases		Computed uncon- trolled ²	Total Discharge	Precipitation	
	Directed release ¹	Pepacton	Cannons- ville	Never- sink	Wallen- paupack	Rio Reservoir			(inches)	
							Daily	Cumul.		
Sept. 10	1,070	178	753	131	0	0	598	1,660	.02	.46
11	681	178	374	131	564	0	833	2,080	.10	.56
12	700	178	387	130	345	0	870	1,910	.85	1.41
13	705	178	398	131	303	0	1,430	2,440	0	1.41
14	654	178	353	131	516	0	1,152	2,330	0	1.41
15	332	139	204	124	315	0	988	1,770	.32	1.73
16	886	124	637	124	0	0	885	1,770	.02	1.75

1. Release directed to maintain a flow at Montague of 1,750 cfs.

2. Includes conservation release from Rio Reservoir.

Divisions by New Jersey through the Delaware and Raritan Canal September 10 - 16, 2007, averaged 91.4 mgd. The average diversion for the 30-day period ending September 16, 2007 was 96.4 mgd and the maximum daily diversion was 105 mg on August 24, 2007.

OFFICE OF THE DELAWARE RIVER MASTER, MILFORD, PA.

Web address: <http://water.usgs.gov/orh/nrwww/odrm>

Summary river data for September 17 - 23, 2007 (preliminary data-subject to revision)

RESERVOIR OPERATION DATA

Millions of gallons - 24 hour period, local time

Date	Discharge to river			Diversions to New York City water supply			
	Pepacton	Cannonsville	Neversink	Pepacton	Cannonsville	Neversink	Average June 1, 2007 to date
	release begin 1200	release end 2400	release begin 1500	beginning 0800	beginning 0800	beginning 0800	
Sept. 17	80	234	80	502	200	0	721
18	70	250	80	501	199	0	721
19	80	279	80	501	199	0	720
20	80	310	80	501	199	0	720
21	90	395	80	501	199	0	720
22	90	571	80	501	200	0	720
23	100	341	80	501	199	0	720

Pepacton Reservoir (P):	Available storage Sept. 24, 2007 (0800) Spillway crest elevation 1,280.00 ft.	98.245 billion gals. 70.1 % (elev. 1,255.14 ft.) 140.190 billion gallons.
Cannonsville Reservoir (C):	Available storage Sept. 24, 2007 (0800) Spillway crest elevation 1,150.00 ft.	51.709 billion gals. 54.0 % (elev. 1,117.29 ft.) 95.706 billion gallons.
Neversink Reservoir (N):	Available storage Sept. 24, 2007 (0800) Spillway crest elevation 1,440.00 ft.	23.597 billion gals. 67.5 % (elev. 1,414.53 ft.) 34.941 billion gallons.
Combined contents, PCN:	Available storage Sept. 24, 2007 (0800) Combined capacity at spillway level.	173.551 billion gals. 64.1 % 270.837 billion gallons.
Lake Wallenpaupack:	Available storage Sept. 23, 2007 (2400) Spillway crest elevation 1,190.00 ft.	15.906 billion gals. 44.9 % (elev. 1,179.3 ft.) 35.451 billion gallons.

SEGREGATION OF FLOW, DELAWARE RIVER AT MONTAGUE AND
PRECIPITATION IN UPPER DELAWARE RIVER BASIN

Discharge in cubic feet per second, local time as routed to Montague

Date	Releases from N.Y.C. Reservoirs				Power releases		Computed uncon- trolled ²	Total Discharge	Precipitation	
	Directed release ¹	Pepacton	Cannons- ville	Never- sink	Wallen- paupack	Rio Reservoir			(inches)	
									Daily	Cumul.
Sept. 17	1,007	124	763	124	0	0	1,049	2,060	0	1.75
18	590	124	345	124	313	0	974	1,880	0	1.75
19	610	124	362	124	192	0	858	1,660	0	1.75
20	636	124	387	124	337	0	728	1,700	0	1.75
21	668	108	432	124	267	0	719	1,650	0	1.75
22	728	124	480	124	271	0	661	1,660	0	1.75
23	859	124	611	124	273	0	618	1,750	0	1.75

1. Release directed to maintain a flow at Montague of 1,750 cfs.

2. Includes conservation release from Rio Reservoir.

Diversions by New Jersey through the Delaware and Raritan Canal September 17 - 23, 2007, averaged 87.0 mgd. The average diversion for the 30-day period ending September 23, 2007 was 94.3 mgd and the maximum daily diversion was 103 mgd on August 25 and 26, 2007.

OFFICE OF THE DELAWARE RIVER MASTER, MILFORD, PA.

Web address: <http://water.usgs.gov/orh/nrwww/odrm>

Summary river data for September 24 - 30, 2007 (preliminary data-subject to revision)

RESERVOIR OPERATION DATA

Millions of gallons - 24 hour period, local time

Date	Discharge to river			Diversions to New York City water supply			
	Pepacton	Cannonsville	Neversink	Pepacton	Cannonsville	Neversink	Average June 1, 2007 to date
	release begin 1200	release end 2400	release begin 1500	beginning 0800	beginning 0800	beginning 0800	
Sept. 24	100	350	80	500	199	0	720
25	105	346	85	500	197	0	719
26	105	582	85	501	195	5	719
27	105	483	85	500	195	0	719
28	105	500	85	501	195	0	719
29	105	576	85	501	195	11	719
30	74	574	85	480	195	0	718

Pepacton Reservoir (P):	Available storage Oct. 1, 2007 (0800)	96.144 billion gals.	68.6 % (elev. 1,253.76 ft.)
	Spillway crest elevation 1,280.00 ft.	140.190 billion gallons.	
Cannonsville Reservoir (C):	Available storage Oct. 1, 2007 (0800)	48.581 billion gals.	50.8 % (elev. 1,114.59 ft.)
	Spillway crest elevation 1,150.00 ft.	95.706 billion gallons.	
Neversink Reservoir (N):	Available storage Oct. 1, 2007 (0800)	23.135 billion gals.	66.2 % (elev. 1,413.37 ft.)
	Spillway crest elevation 1,440.00 ft.	34.941 billion gallons.	
Combined contents, PCN:	Available storage Oct. 1, 2007 (0800)	167.860 billion gals.	62.0 %
	Combined capacity at spillway level.	270.837 billion gallons.	
Lake Wallenpaupack:	Available storage Sept. 30, 2007 (2400)	15.026 billion gals.	42.4 % (elev. 1,178.8 ft.)
	Spillway crest elevation 1,190.00 ft.	35.451 billion gallons.	

SEGREGATION OF FLOW, DELAWARE RIVER AT MONTAGUE AND
PRECIPITATION IN UPPER DELAWARE RIVER BASIN

Discharge in cubic feet per second, local time as routed to Montague

Date	Releases from N.Y.C. Reservoirs				Power releases		Computed uncon- trolled ²	Total Discharge	Precipitation	
	Directed release ¹	Pepacton	Cannons- ville	Never- sink	Wallen- paupack	Rio Reservoir			(inches)	
							Daily	Cumul.		
Sept. 24	1,152	139	883	124	0	0	614	1,760	0	1.75
25	788	139	528	124	323	0	636	1,750	0	1.75
26	820	155	541	124	327	0	563	1,710	0	1.75
27	822	155	535	131	484	0	605	1,910	.02	1.77
28	1,189	162	900	131	0	0	507	1,700	.47	2.24
29	1,042	162	747	131	0	0	620	1,660	.10	2.34
30	1,065	162	774	131	0	0	783	1,850	0	2.34

1. Release directed to maintain a flow at Montague of 1,750 cfs.

2. Includes conservation release from Rio Reservoir.

Diversions by New Jersey through the Delaware and Raritan Canal September 24 - 30, 2007, averaged 87.7 mgd. The average diversion for the 30-day period ending September 30, 2007 was 91.1 mgd and the maximum daily diversion was 99 mg on September 3, 2007.

OFFICE OF THE DELAWARE RIVER MASTER, MILFORD, PA.

Web address: <http://water.usgs.gov/orh/nrwww/odrm>

Summary river data for October 1 - 7, 2007 (preliminary data-subject to revision)

RESERVOIR OPERATION DATA

Millions of gallons - 24 hour period, local time

Date	Discharge to river			Diversions to New York City water supply			
	Pepacton	Cannonsville	Neversink	Pepacton	Cannonsville	Neversink	Average June 1, 2007 to date
	release begin 1200	release end 2400	release begin 1500	beginning 0800	beginning 0800	beginning 0800	
Oct. 1	55	664	45	0	289	82	716
2	55	693	45	0	296	123	713
3	55	708	45	311	296	109	713
4	55	711	45	498	293	0	714
5	55	794	45	500	195	0	714
6	55	801	45	500	194	0	713
7	55	804	45	456	178	0	713

Pepacton Reservoir (P):	Available storage Oct. 8, 2007 (0800)	94.725 billion gals.	67.6 % (elev. 1,252.82 ft.)
	Spillway crest elevation 1,280.00 ft.	140.190 billion gallons.	
Cannonsville Reservoir (C):	Available storage Oct. 8, 2007 (0800)	42.973 billion gals.	44.9 % (elev. 1,109.52 ft.)
	Spillway crest elevation 1,150.00 ft.	95.706 billion gallons.	
Neversink Reservoir (N):	Available storage Oct. 8, 2007 (0800)	22.630 billion gals.	64.8 % (elev. 1,412.09 ft.)
	Spillway crest elevation 1,440.00 ft.	34.941 billion gallons.	
Combined contents, PCN:	Available storage Oct. 8, 2007 (0800)	160.328 billion gals.	59.2 %
	Combined capacity at spillway level.	270.837 billion gallons.	
Lake Wallenpaupack:	Available storage Oct. 7, 2007 (2400)	16.610 billion gals.	46.9 % (elev. 1,179.7 ft.)
	Spillway crest elevation 1,190.00 ft.	35.451 billion gallons.	

SEGREGATION OF FLOW, DELAWARE RIVER AT MONTAGUE AND
PRECIPITATION IN UPPER DELAWARE RIVER BASIN

Discharge in cubic feet per second, local time as routed to Montague

Date	Releases from N.Y.C. Reservoirs				Power releases		Computed uncon- trolled ²	Total Discharge	Precipitation	
	Directed release ¹	Pepacton	Cannons- ville	Never- sink	Wallen- paupack	Rio Reservoir			(inches)	
									Daily	Cumul.
Oct. 1	1,190	162	891	131	0	0	636	1,820	0	0
2	1,197	162	888	131	0	0	609	1,790	0	0
3	1,208	114	1,027	70	0	0	569	1,780	0	0
4	1,230	85	1,072	70	0	0	533	1,760	0	0
5	1,252	85	1,095	70	0	0	510	1,760	0	0
6	1,258	85	1,100	70	0	0	515	1,770	0	0
7	1,389	85	1,228	70	0	0	477	1,860	.13	.13

1. Release directed to maintain a flow at Montague of 1,750 cfs. Directed release on October 7 includes an additional 100 cfs to support the Trenton flow objective.

2. Includes conservation release from Rio Reservoir.

Diversions by New Jersey through the Delaware and Raritan Canal October 1 - 7, 2007, averaged 91.1 mgd. The average diversion for the 30-day period ending October 7, 2007 was 89.8 mgd and the maximum daily diversion was 96 mg on September 8, 9, and 10, 2007.

OFFICE OF THE DELAWARE RIVER MASTER, MILFORD, PA.

Web address: <http://water.usgs.gov/orh/nrwww/odrm>

Summary river data for October 8 - 14, 2007 (preliminary data-subject to revision)

RESERVOIR OPERATION DATA

Millions of gallons - 24 hour period, local time

Date	Discharge to river			Diversions to New York City water supply			
	Pepacton	Cannonsville	Neversink	Pepacton	Cannonsville	Neversink	Average June 1, 2007 to date
	release begin 1200	release end 2400	release begin 1500	beginning 0800	beginning 0800	beginning 0800	
Oct. 8	55	753	45	393	162	0	712
9	54	565	45	500	245	0	712
10	54	395	45	500	196	0	712
11	40	161	45	500	19	0	710
12	40	56	29	501	0	0	709
13	40	52	29	501	0	0	707
14	40	52	29	500	0	0	706

Pepacton Reservoir (P):	Available storage Oct. 15, 2007 (0800)	93.557 billion gals.	66.7 % (elev. 1,252.04 ft.)
	Spillway crest elevation 1,280.00 ft.	140.190 billion gallons.	
Cannonsville Reservoir (C):	Available storage Oct. 15, 2007 (0800)	43.435 billion gals.	45.4 % (elev. 1,109.96 ft.)
	Spillway crest elevation 1,150.00 ft.	95.706 billion gallons.	
Neversink Reservoir (N):	Available storage Oct. 15, 2007 (0800)	22.713 billion gals.	65.0 % (elev. 1,412.30 ft.)
	Spillway crest elevation 1,440.00 ft.	34.941 billion gallons.	
Combined contents, PCN:	Available storage Oct. 15, 2007 (0800)	159.705 billion gals.	59.0 %
	Combined capacity at spillway level.	270.837 billion gallons.	
Lake Wallenpaupack:	Available storage Oct. 14, 2007 (2400)	15.378 billion gals.	43.4 % (elev. 1,179.0 ft.)
	Spillway crest elevation 1,190.00 ft.	35.451 billion gallons.	

SEGREGATION OF FLOW, DELAWARE RIVER AT MONTAGUE AND
PRECIPITATION IN UPPER DELAWARE RIVER BASIN

Discharge in cubic feet per second, local time as routed to Montague

Date	Releases from N.Y.C. Reservoirs				Power releases		Computed uncon- trolled ²	Total Discharge	Precipitation	
	Directed release ¹	Pepacton	Cannons- ville	Never- sink	Wallen- paupack	Rio Reservoir			(inches)	
							Daily	Cumul.		
Oct. 8	1,394	85	1,239	70	0	0	496	1,890	0	.13
9	1,405	85	1,244	70	0	0	541	1,940	.14	.27
10	1,319	85	1,165	70	0	0	990	2,310	1.41	1.68
11	1,027	85	874	70	0	0	1,701	2,730	.32	2.00
12	765	84	611	70	196	0	4,019	4,980	1.58	3.58
13	403	84	249	70	0	0	4,807	5,210	.01	3.59
14	0	62	87	45	0	0	3,156	3,350	0	3.59

1. Release directed to maintain a flow at Montague of 1,750 cfs. Directed releases on October 8 - 11 include an additional 100 cfs to support the Trenton flow objective.

2. Includes conservation release from Rio Reservoir.

Diversions by New Jersey through the Delaware and Raritan Canal October 8 - 14, 2007, averaged 91.6 mgd. The average diversion for the 30-day period ending October 14, 2007 was 89.3 mgd and the maximum daily diversion was 96 mg on October 10, 2007.

OFFICE OF THE DELAWARE RIVER MASTER, MILFORD, PA.

Web address: <http://water.usgs.gov/orh/nrwww/odrm>

Summary river data for October 15 - 21, 2007 (preliminary data-subject to revision)

RESERVOIR OPERATION DATA

Millions of gallons - 24 hour period, local time

Date	Discharge to river			Diversions to New York City water supply			
	Pepacton	Cannonsville	Neversink	Pepacton	Cannonsville	Neversink	Average June 1, 2007 to date
	release begin 1200	release end 2400	release begin 1500	beginning 0800	beginning 0800	beginning 0800	
Oct. 15	39	52	29	500	0	0	704
16	39	53	29	500	0	0	703
17	39	131	29	500	0	0	701
18	39	54	29	500	0	48	700
19	38	52	29	500	0	0	699
20	39	219	29	500	0	0	697
21	39	58	29	500	0	0	696

Pepacton Reservoir (P):	Available storage Oct. 22, 2007 (0800)	92.620 billion gals.	66.1 % (elev. 1,251.41 ft.)
	Spillway crest elevation 1,280.00 ft.	140.190 billion gallons.	
Cannonsville Reservoir (C):	Available storage Oct. 22, 2007 (0800)	45.390 billion gals.	47.4 % (elev. 1,111.72 ft.)
	Spillway crest elevation 1,150.00 ft.	95.706 billion gallons.	
Neversink Reservoir (N):	Available storage Oct. 22, 2007 (0800)	23.219 billion gals.	66.5 % (elev. 1,413.58 ft.)
	Spillway crest elevation 1,440.00 ft.	34.941 billion gallons.	
Combined contents, PCN:	Available storage Oct. 22, 2007 (0800)	161.229 billion gals.	59.5 %
	Combined capacity at spillway level.	270.837 billion gallons.	
Lake Wallenpaupack:	Available storage Oct. 21, 2007 (2400)	16.258 billion gals.	45.9 % (elev. 1,179.5 ft.)
	Spillway crest elevation 1,190.00 ft.	35.451 billion gallons.	

SEGREGATION OF FLOW, DELAWARE RIVER AT MONTAGUE AND
PRECIPITATION IN UPPER DELAWARE RIVER BASIN

Discharge in cubic feet per second, local time as routed to Montague

Date	Releases from N.Y.C. Reservoirs				Power releases		Computed uncon- trolled ²	Total Discharge	Precipitation	
	Directed release ¹	Pepacton	Cannons- ville	Never- sink	Wallen- paupack	Rio Reservoir			(inches)	
									Daily	Cumul.
Oct. 15	0	62	80	45	0	0	2,353	2,540	0	3.59
16	0	62	80	45	0	0	1,933	2,120	0	3.59
17	0	62	80	45	0	0	1,643	1,830	0	3.59
18	108	60	82	45	0	0	1,423	1,610	0	3.59
19	304	60	203	45	9	0	1,233	1,550	0	3.59
20	0	60	84	45	0	0	2,151	2,340	.99	4.58
21	0	60	80	45	0	0	3,265	3,450	.01	4.59

1. Release directed to maintain a flow at Montague of 1,750 cfs.

2. Includes conservation release from Rio Reservoir.

Diversions by New Jersey through the Delaware and Raritan Canal October 15 - 21, 2007, averaged 89.7 mgd. The average diversion for the 30-day period ending October 21, 2007 was 89.9 mgd and the maximum daily diversion was 96 mg on October 10, 2007.

OFFICE OF THE DELAWARE RIVER MASTER, MILFORD, PA.

Web address: <http://water.usgs.gov/orh/nrwww/odrm>

Summary river data for October 22 - 28, 2007 (preliminary data-subject to revision)

RESERVOIR OPERATION DATA

Millions of gallons - 24 hour period, local time

Date	Discharge to river			Diversions to New York City water supply			
	Pepacton	Cannonsville	Neversink	Pepacton	Cannonsville	Neversink	Average June 1, 2007 to date
	release begin 1200	release end 2400	release begin 1500	beginning 0800	beginning 0800	beginning 0800	
Oct. 22	39	52	29	500	0	0	695
23	39	52	29	501	176	2	695
24	39	53	29	456	195	0	694
25	39	52	29	500	212	0	694
26	39	52	29	506	212	0	694
27	39	52	29	507	200	0	695
28	39	52	29	509	5	0	693

Pepacton Reservoir (P):	Available storage Oct. 29, 2007 (0800) Spillway crest elevation 1,280.00 ft.	96.204 billion gals. 68.6 % (elev. 1,253.80 ft.) 140.190 billion gallons.
Cannonsville Reservoir (C):	Available storage Oct. 29, 2007 (0800) Spillway crest elevation 1,150.00 ft.	51.126 billion gals. 53.4 % (elev. 1,116.79 ft.) 95.706 billion gallons.
Neversink Reservoir (N):	Available storage Oct. 29, 2007 (0800) Spillway crest elevation 1,440.00 ft.	25.118 billion gals. 71.9 % (elev. 1,418.27 ft.) 34.941 billion gallons.
Combined contents, PCN:	Available storage Oct. 29, 2007 (0800) Combined capacity at spillway level.	172.448 billion gals. 63.7 % 270.837 billion gallons.
Lake Wallenpaupack:	Available storage Oct. 28, 2007 (2400) Spillway crest elevation 1,190.00 ft.	19.077 billion gals. 53.8 % (elev. 1,181.1 ft.) 35.451 billion gallons.

SEGREGATION OF FLOW, DELAWARE RIVER AT MONTAGUE AND
PRECIPITATION IN UPPER DELAWARE RIVER BASIN

Discharge in cubic feet per second, local time as routed to Montague

Date	Releases from N.Y.C. Reservoirs				Power releases		Computed uncon- trolled ²	Total Discharge	Precipitation	
	Directed release ¹	Pepacton	Cannons- ville	Never- sink	Wallen- paupack	Rio Reservoir			(inches)	
							Daily	Cumul.		
Oct. 22	445	59	339	45	0	0	2,847	3,290	0	4.59
23	0	60	90	45	0	0	2,275	2,470	0	4.59
24	0	60	80	45	0	0	2,045	2,230	.55	5.14
25	0	60	80	45	0	0	2,825	3,010	.22	5.36
26	0	60	82	45	0	0	3,323	3,510	0	5.36
27	0	60	80	45	0	0	4,455	4,640	.83	6.19
28	0	60	80	45	0	0	16,315	16,500	.82	7.01

1. Release directed to maintain a flow at Montague of 1,750 cfs.

2. Includes conservation release from Rio Reservoir.

Diversions by New Jersey through the Delaware and Raritan Canal October 22 - 28, 2007, averaged 84.7 mgd. The average diversion for the 30-day period ending October 28, 2007 was 89.2 mgd and the maximum daily diversion was 96 mg on October 10, 2007.

OFFICE OF THE DELAWARE RIVER MASTER, MILFORD, PA.

Web address: <http://water.usgs.gov/orh/nrwww/odrm>

Summary river data for November 5 - 11, 2007 (preliminary data-subject to revision)

RESERVOIR OPERATION DATA

Millions of gallons - 24 hour period, local time

Date	Discharge to river			Diversions to New York City water supply			
	Pepacton	Cannonsville	Neversink	Pepacton	Cannonsville	Neversink	Average June 1, 2007 to date
	release begin 1200	release end 2400	release begin 1500	beginning 0800	beginning 0800	beginning 0800	
Nov. 5	39	52	29	502	0	0	684
6	39	52	29	502	0	0	683
7	39	52	29	502	0	0	682
8	39	52	29	502	176	200	683
9	39	53	29	501	190	146	684
10	39	53	29	501	0	148	684
11	39	53	29	501	9	147	683

Pepacton Reservoir (P):	Available storage Nov. 12, 2007 (0800) Spillway crest elevation 1,280.00 ft.	97.115 billion gals. 69.3 % (elev. 1,254.40 ft.) 140.190 billion gallons.
Cannonsville Reservoir (C):	Available storage Nov. 12, 2007 (0800) Spillway crest elevation 1,150.00 ft.	60.048 billion gals. 62.7 % (elev. 1,124.24 ft.) 95.706 billion gallons.
Neversink Reservoir (N):	Available storage Nov. 12, 2007 (0800) Spillway crest elevation 1,440.00 ft.	25.834 billion gals. 73.9 % (elev. 1,419.99 ft.) 34.941 billion gallons.
Combined contents, PCN:	Available storage Nov. 12, 2007 (0800) Combined capacity at spillway level.	182.997 billion gals. 67.6 % 270.837 billion gallons.
Lake Wallenpaupack:	Available storage Nov. 11, 2007 (2400) Spillway crest elevation 1,190.00 ft.	19.794 billion gals. 55.8 % (elev. 1,181.5 ft.) 35.451 billion gallons.

SEGREGATION OF FLOW, DELAWARE RIVER AT MONTAGUE AND
PRECIPITATION IN UPPER DELAWARE RIVER BASIN

Discharge in cubic feet per second, local time as routed to Montague

Date	Releases from N.Y.C. Reservoirs				Power releases		Computed uncon- trolled ²	Total Discharge	Precipitation	
	Directed release ¹	Pepacton	Cannons- ville	Never- sink	Wallen- paupack	Rio Reservoir			(inches)	
							Daily	Cumul.		
Nov. 5	0	60	80	46	15	0	2,799	3,000	0	0
6	0	63	84	45	249	0	2,639	3,080	.36	.36
7	0	60	80	45	301	18	2,816	3,320	.01	.37
8	0	60	80	45	252	89	3,094	3,620	0	.37
9	0	60	80	45	233	177	2,595	3,190	0	.37
10	0	60	80	45	259	89	2,427	2,960	.19	.56
11	0	60	82	45	0	0	2,443	2,630	.03	.59

1. Release directed to maintain a flow at Montague of 1,750 cfs.

2. Includes conservation release from Rio Reservoir.

Diversions by New Jersey through the Delaware and Raritan Canal November 5 - 11, 2007, averaged 90.3 mgd. The average diversion for the 30-day period ending November 11, 2007 was 88.4 mgd and the maximum daily diversion was 95 mg on October 17, 2007.

OFFICE OF THE DELAWARE RIVER MASTER, MILFORD, PA.

Web address: <http://water.usgs.gov/orh/nrwww/odrm>

Summary river data for November 12 - 18, 2007 (preliminary data-subject to revision)

RESERVOIR OPERATION DATA

Millions of gallons - 24 hour period, local time

Date	Discharge to river			Diversions to New York City water supply			
	Pepacton	Cannonsville	Neversink	Pepacton	Cannonsville	Neversink	Average June 1, 2007 to date
	release begin 1200	release end 2400	release begin 1500	beginning 0800	beginning 0800	beginning 0800	
Nov. 12	39	53	29	464	123	147	684
13	39	52	29	334	0	0	682
14	39	51	29	499	0	0	680
15	39	51	29	500	0	0	679
16	39	52	29	502	0	0	678
17	40	53	29	502	0	0	677
18	39	52	29	464	0	0	676

Pepacton Reservoir (P):	Available storage Nov. 19, 2007 (0800)	101.538 billion gals.	72.4 % (elev. 1,257.27 ft.)
	Spillway crest elevation 1,280.00 ft.	140.190 billion gallons.	
Cannonsville Reservoir (C):	Available storage Nov. 19, 2007 (0800)	66.477 billion gals.	69.5 % (elev. 1,129.32 ft.)
	Spillway crest elevation 1,150.00 ft.	95.706 billion gallons.	
Neversink Reservoir (N):	Available storage Nov. 19, 2007 (0800)	28.076 billion gals.	80.4 % (elev. 1,425.24 ft.)
	Spillway crest elevation 1,440.00 ft.	34.941 billion gallons.	
Combined contents, PCN:	Available storage Nov. 19, 2007 (0800)	196.091 billion gals.	72.4 %
	Combined capacity at spillway level.	270.837 billion gallons.	
Lake Wallenpaupack:	Available storage Nov. 18, 2007 (2400)	21.765 billion gals.	61.4 % (elev. 1,182.6 ft.)
	Spillway crest elevation 1,190.00 ft.	35.451 billion gallons.	

SEGREGATION OF FLOW, DELAWARE RIVER AT MONTAGUE AND
PRECIPITATION IN UPPER DELAWARE RIVER BASIN

Discharge in cubic feet per second, local time as routed to Montague

Date	Releases from N.Y.C. Reservoirs				Power releases		Computed uncon- trolled ²	Total Discharge	Precipitation	
	Directed release ¹	Pepacton	Cannons- ville	Never- sink	Wallen- paupack	Rio Reservoir			(inches)	
							Daily	Cumul.		
Nov. 12	0	60	82	45	0	0	2,403	2,590	0	.59
13	0	60	82	45	312	160	2,321	2,980	.38	.97
14	0	60	82	45	367	230	3,086	3,870	0	.97
15	0	60	80	45	297	230	6,408	7,120	1.08	2.05
16	0	60	79	45	291	762	18,563	19,800	.37	2.42
17	0	60	79	45	227	851	12,438	13,700	.01	2.43
18	0	60	80	45	135	851	8,489	9,660	0	2.43

1. Release directed to maintain a flow at Montague of 1,750 cfs.

2. Includes conservation release from Rio Reservoir.

Diversions by New Jersey through the Delaware and Raritan Canal November 12 - 18, 2007, averaged 89.0 mgd. The average diversion for the 30-day period ending November 18, 2007 was 87.9 mgd and the maximum daily diversion was 93 mg on November 1 and 15, 2007.

OFFICE OF THE DELAWARE RIVER MASTER, MILFORD, PA.

Web address: <http://water.usgs.gov/orh/nrwww/odrm>

Summary river data for November 19 - 25, 2007 (preliminary data-subject to revision)

RESERVOIR OPERATION DATA

Millions of gallons - 24 hour period, local time

Date	Discharge to river			Diversions to New York City water supply			
	Pepacton	Cannonsville	Neversink	Pepacton	Cannonsville	Neversink	Average June 1, 2007 to date
	release begin 1200	release end 2400	release begin 1500	beginning 0800	beginning 0800	beginning 0800	
Nov. 19	39	52	29	3	0	0	672
20	40	52	29	0	0	0	668
21	40	53	29	72	0	0	665
22	41	53	31	490	0	0	664
23	55	64	39	490	0	0	663
24	55	71	39	494	0	0	662
25	55	71	39	454	0	0	661

Pepacton Reservoir (P):	Available storage Nov. 26, 2007 (0800)	104.875 billion gals.	74.8 % (elev. 1,259.39 ft.)
	Spillway crest elevation 1,280.00 ft.	140.190 billion gallons.	
Cannonsville Reservoir (C):	Available storage Nov. 26, 2007 (0800)	72.391 billion gals.	75.6 % (elev. 1,133.81 ft.)
	Spillway crest elevation 1,150.00 ft.	95.706 billion gallons.	
Neversink Reservoir (N):	Available storage Nov. 26, 2007 (0800)	29.248 billion gals.	83.7 % (elev. 1,427.90 ft.)
	Spillway crest elevation 1,440.00 ft.	34.941 billion gallons.	
Combined contents, PCN:	Available storage Nov. 26, 2007 (0800)	206.514 billion gals.	76.3 %
	Combined capacity at spillway level.	270.837 billion gallons.	
Lake Wallenpaupack:	Available storage Nov. 25, 2007 (2400)	22.482 billion gals.	63.4 % (elev. 1,183.0 ft.)
	Spillway crest elevation 1,190.00 ft.	35.451 billion gallons.	

SEGREGATION OF FLOW, DELAWARE RIVER AT MONTAGUE AND
PRECIPITATION IN UPPER DELAWARE RIVER BASIN

Discharge in cubic feet per second, local time as routed to Montague

Date	Releases from N.Y.C. Reservoirs				Power releases		Computed uncon- trolled ²	Total Discharge	Precipitation	
	Directed release ¹	Pepacton	Cannons- ville	Never- sink	Wallen- paupack	Rio Reservoir			(inches)	
							Daily	Cumul.		
Nov. 19	0	60	82	45	154	408	6,861	7,610	.13	2.56
20	0	62	80	45	399	426	6,138	7,150	.16	2.72
21	0	60	80	45	553	496	7,496	8,730	.14	2.86
22	0	60	80	45	638	603	7,054	8,480	.03	2.89
23	0	62	82	45	280	408	6,183	7,060	0	2.89
24	0	62	82	48	312	426	5,310	6,240	0	2.89
25	0	63	99	60	338	426	4,644	5,630	0	2.89

1. Release directed to maintain a flow at Montague of 1,750 cfs.

2. Includes conservation release from Rio Reservoir.

Diversions by New Jersey through the Delaware and Raritan Canal November 19 - 25, 2007, averaged 92.1 mgd. The average diversion for the 30-day period ending November 25, 2007 was 88.8 mgd and the maximum daily diversion was 96 mg on November 22, 2007.

OFFICE OF THE DELAWARE RIVER MASTER, MILFORD, PA.

Web address: <http://water.usgs.gov/orh/nrwww/odrm>

Summary river data for November 26 - December 2, 2007 (preliminary data-subject to revision)

RESERVOIR OPERATION DATA

Millions of gallons - 24 hour period, local time

Date	Discharge to river			Diversions to New York City water supply			
	Pepacton	Cannonsville	Neversink	Pepacton	Cannonsville	Neversink	Average June 1, 2007 to date
	release begin 1200	release end 2400	release begin 1500	beginning 0800	beginning 0800	beginning 0800	
Nov. 26	55	71	39	0	0	0	657
27	55	72	39	0	185	228	656
28	55	71	39	0	226	266	655
29	56	71	39	330	49	64	654
30	53	72	39	498	0	0	653
Dec. 1	56	71	39	502	0	0	652
2	56	72	40	461	0	0	651

Pepacton Reservoir (P):	Available storage Dec. 3, 2007 (0800)	109.543 billion gals.	78.1 % (elev. 1,262.30 ft.)
	Spillway crest elevation 1,280.00 ft.	140.190 billion gallons.	
Cannonsville Reservoir (C):	Available storage Dec. 3, 2007 (0800)	80.115 billion gals.	83.7 % (elev. 1,139.45 ft.)
	Spillway crest elevation 1,150.00 ft.	95.706 billion gallons.	
Neversink Reservoir (N):	Available storage Dec. 3, 2007 (0800)	30.346 billion gals.	86.8 % (elev. 1,430.33 ft.)
	Spillway crest elevation 1,440.00 ft.	34.941 billion gallons.	
Combined contents, PCN:	Available storage Dec. 3, 2007 (0800)	220.004 billion gals.	81.2 %
	Combined capacity at spillway level.	270.837 billion gallons.	
Lake Wallenpaupack:	Available storage Dec. 2, 2007 (2400)	22.847 billion gals.	64.4 % (elev. 1,183.2 ft.)
	Spillway crest elevation 1,190.00 ft.	35.451 billion gallons.	

SEGREGATION OF FLOW, DELAWARE RIVER AT MONTAGUE AND
PRECIPITATION IN UPPER DELAWARE RIVER BASIN

Discharge in cubic feet per second, local time as routed to Montague

Date	Releases from N.Y.C. Reservoirs				Power releases		Computed uncon- trolled ²	Total Discharge	Precipitation	
	Directed release ¹	Pepacton	Cannons- ville	Never- sink	Wallen- paupack	Rio Reservoir			(inches)	
							Daily	Cumul.		
Nov. 26	0	85	110	60	388	532	5,385	6,560	.46	3.35
27	0	85	110	60	863	727	11,055	12,900	.79	4.14
28	0	85	110	60	1,085	745	13,315	15,400	0	4.14
29	0	85	111	60	1,189	567	9,588	11,600	0	4.14
30	0	85	110	60	1,039	390	7,706	9,390	.01	4.15
Dec. 1	0	85	110	60	681	656	6,288	7,880	0	0
2	0	87	111	60	508	426	5,488	6,680	.09	.09

1. Release directed to maintain a flow at Montague of 1,750 cfs.

2. Includes conservation release from Rio Reservoir.

Diversions by New Jersey through the Delaware and Raritan Canal November 26 - December 2, 2007, averaged 93.7 mgd. The average diversion for the 30-day period ending December 2, 2007 was 91.3 mgd and the maximum daily diversion was 96 mg on November 22, 30, and December 1, 2007.

OFFICE OF THE DELAWARE RIVER MASTER, MILFORD, PA.

Web address: <http://water.usgs.gov/orh/nrwww/odrm>

Summary river data for November 26 - December 2, 2007 (preliminary data-subject to revision)

RESERVOIR OPERATION DATA

Millions of gallons - 24 hour period, local time

Date	Discharge to river			Diversions to New York City water supply			
	Pepacton	Cannonsville	Neversink	Pepacton	Cannonsville	Neversink	Average June 1, 2007 to date
	release begin 1200	release end 2400	release begin 1500	beginning 0800	beginning 0800	beginning 0800	
Nov. 26	55	71	39	0	0	0	657
27	55	72	39	0	185	228	656
28	55	71	39	0	226	266	655
29	56	71	39	330	49	64	654
30	53	72	39	498	0	0	653
Dec. 1	56	71	39	502	0	0	652
2	56	72	40	461	0	0	651

Pepacton Reservoir (P):	Available storage Dec. 3, 2007 (0800)	109.543 billion gals.	78.1 % (elev. 1,262.30 ft.)
	Spillway crest elevation 1,280.00 ft.	140.190 billion gallons.	
Cannonsville Reservoir (C):	Available storage Dec. 3, 2007 (0800)	80.115 billion gals.	83.7 % (elev. 1,139.45 ft.)
	Spillway crest elevation 1,150.00 ft.	95.706 billion gallons.	
Neversink Reservoir (N):	Available storage Dec. 3, 2007 (0800)	30.346 billion gals.	86.8 % (elev. 1,430.33 ft.)
	Spillway crest elevation 1,440.00 ft.	34.941 billion gallons.	
Combined contents, PCN:	Available storage Dec. 3, 2007 (0800)	220.004 billion gals.	81.2 %
	Combined capacity at spillway level.	270.837 billion gallons.	
Lake Wallenpaupack:	Available storage Dec. 2, 2007 (2400)	22.847 billion gals.	64.4 % (elev. 1,183.2 ft.)
	Spillway crest elevation 1,190.00 ft.	35.451 billion gallons.	

SEGREGATION OF FLOW, DELAWARE RIVER AT MONTAGUE AND
PRECIPITATION IN UPPER DELAWARE RIVER BASIN

Discharge in cubic feet per second, local time as routed to Montague

Date	Releases from N.Y.C. Reservoirs				Power releases		Computed uncon- trolled ²	Total Discharge	Precipitation	
	Directed release ¹	Pepacton	Cannons- ville	Never- sink	Wallen- paupack	Rio Reservoir			(inches)	
							Daily	Cumul.		
Nov. 26	0	85	110	60	388	532	5,385	6,560	.46	3.35
27	0	85	110	60	863	727	11,055	12,900	.79	4.14
28	0	85	110	60	1,085	745	13,315	15,400	0	4.14
29	0	85	111	60	1,189	567	9,588	11,600	0	4.14
30	0	85	110	60	1,039	390	7,706	9,390	.01	4.15
Dec. 1	0	85	110	60	681	656	6,288	7,880	0	0
2	0	87	111	60	508	426	5,488	6,680	.09	.09

1. Release directed to maintain a flow at Montague of 1,750 cfs.

2. Includes conservation release from Rio Reservoir.

Diversions by New Jersey through the Delaware and Raritan Canal November 26 - December 2, 2007, averaged 93.7 mgd. The average diversion for the 30-day period ending December 2, 2007 was 91.3 mgd and the maximum daily diversion was 96 mg on November 22, 30, and December 1, 2007.

OFFICE OF THE DELAWARE RIVER MASTER, MILFORD, PA.

Web address: <http://water.usgs.gov/orh/nrwww/odrm>

Summary river data for December 3 - 9, 2007 (preliminary data-subject to revision)

RESERVOIR OPERATION DATA

Millions of gallons - 24 hour period, local time

Date	Discharge to river			Diversions to New York City water supply			
	Pepacton	Cannonsville	Neversink	Pepacton	Cannonsville	Neversink	Average June 1, 2007 to date
	release begin 1200	release end 2400	release begin 1500	beginning 0800	beginning 0800	beginning 0800	
Dec. 3	55	71	42	415	0	0	650
4	55	71	42	0	0	0	646
5	55	71	42	0	0	0	643
6	55	72	42	290	0	2	641
7	55	71	42	502	0	197	641
8	55	71	42	503	0	195	641
9	55	71	42	462	0	173	641

Pepacton Reservoir (P):	Available storage Dec. 10, 2007 (0800)	110.794 billion gals.	79.0 % (elev. 1,263.07 ft.)
	Spillway crest elevation 1,280.00 ft.	140.190 billion gallons.	
Cannonsville Reservoir (C):	Available storage Dec. 10, 2007 (0800)	84.299 billion gals.	88.1 % (elev. 1,142.37 ft.)
	Spillway crest elevation 1,150.00 ft.	95.706 billion gallons.	
Neversink Reservoir (N):	Available storage Dec. 10, 2007 (0800)	30.621 billion gals.	87.6 % (elev. 1,430.93 ft.)
	Spillway crest elevation 1,440.00 ft.	34.941 billion gallons.	
Combined contents, PCN:	Available storage Dec. 10, 2007 (0800)	225.714 billion gals.	83.3 %
	Combined capacity at spillway level.	270.837 billion gallons.	
Lake Wallenpaupack:	Available storage Dec. 9, 2007 (2400)	22.482 billion gals.	63.4 % (elev. 1,183.0 ft.)
	Spillway crest elevation 1,190.00 ft.	35.451 billion gallons.	

SEGREGATION OF FLOW, DELAWARE RIVER AT MONTAGUE AND
PRECIPITATION IN UPPER DELAWARE RIVER BASIN

Discharge in cubic feet per second, local time as routed to Montague

Date	Releases from N.Y.C. Reservoirs				Power releases		Computed uncon- trolled ²	Total Discharge	Precipitation	
	Directed release ¹	Pepacton	Cannons- ville	Never- sink	Wallen- paupack	Rio Reservoir			(inches)	
							Daily	Cumul.		
Dec. 3	0	82	110	60	535	461	5,262	6,510	.46	.55
4	0	87	111	62	598	532	6,200	7,590	.03	.58
5	0	87	110	65	476	532	5,470	6,740	0	.58
6	0	85	110	65	519	532	4,589	5,900	.02	.60
7	0	85	110	65	515	496	3,959	5,230	0	.60
8	0	85	111	65	418	496	3,635	4,810	.04	.64
9	0	85	110	65	218	461	3,831	4,770	.01	.65

1. Release directed to maintain a flow at Montague of 1,750 cfs.

2. Includes conservation release from Rio Reservoir.

Diversions by New Jersey through the Delaware and Raritan Canal December 3 - 9, 2007, averaged 93.6 mgd. The average diversion for the 30-day period ending December 9, 2007 was 88.8 mgd and the maximum daily diversion was 97 mg on December 3, 4, 2007.

OFFICE OF THE DELAWARE RIVER MASTER, MILFORD, PA.

Web address: <http://water.usgs.gov/orh/nrwww/odrm>

Summary river data for December 10 - 16, 2007 (preliminary data-subject to revision)

RESERVOIR OPERATION DATA

Millions of gallons - 24 hour period, local time

Date	Discharge to river			Diversions to New York City water supply			
	Pepacton	Cannonsville	Neversink	Pepacton	Cannonsville	Neversink	Average June 1, 2007 to date
	release begin 1200	release end 2400	release begin 1500	beginning 0800	beginning 0800	beginning 0800	
Dec. 10	55	72	42	0	0	189	639
11	55	72	42	0	0	267	637
12	55	70	42	0	0	267	635
13	55	122	42	414	0	332	636
14	55	160	42	85	0	352	635
15	55	161	42	0	0	354	633
16	55	161	42	0	0	323	632

Pepacton Reservoir (P):	Available storage Dec. 17, 2007 (0800) Spillway crest elevation 1,280.00 ft.	114.595 billion gals. 81.7 % (elev. 1,265.38 ft.) 140.190 billion gallons.
Cannonsville Reservoir (C):	Available storage Dec. 17, 2007 (0800) Spillway crest elevation 1,150.00 ft.	89.423 billion gals. 93.4 % (elev. 1,145.87 ft.) 95.706 billion gallons.
Neversink Reservoir (N):	Available storage Dec. 17, 2007 (0800) Spillway crest elevation 1,440.00 ft.	29.432 billion gals. 84.2 % (elev. 1,428.31 ft.) 34.941 billion gallons.
Combined contents, PCN:	Available storage Dec. 17, 2007 (0800) Combined capacity at spillway level.	233.450 billion gals. 86.2 % 270.837 billion gallons.
Lake Wallenpaupack:	Available storage Dec. 16, 2007 (2400) Spillway crest elevation 1,190.00 ft.	23.577 billion gals. 66.5 % (elev. 1,183.6 ft.) 35.451 billion gallons.

SEGREGATION OF FLOW, DELAWARE RIVER AT MONTAGUE AND
PRECIPITATION IN UPPER DELAWARE RIVER BASIN

Discharge in cubic feet per second, local time as routed to Montague

Date	Releases from N.Y.C. Reservoirs				Power releases		Computed uncon- trolled ²	Total Discharge	Precipitation	
	Directed release ¹	Pepacton	Cannons- ville	Never- sink	Wallen- paupack	Rio Reservoir			(inches)	
							Daily	Cumul.		
Dec. 10	0	85	110	65	206	461	3,783	4,710	.27	.92
11	0	85	110	65	442	213	4,025	4,940	.01	.93
12	0	85	111	65	534	248	4,517	5,560	.32	1.25
13	0	85	111	65	471	284	7,854	8,870	.02	1.27
14	0	85	108	65	379	532	6,971	8,140	.78	2.05
15	0	85	189	65	246	567	5,928	7,080	0	2.05
16	0	85	248	65	398	284	5,400	6,480	.46	2.51

1. Release directed to maintain a flow at Montague of 1,750 cfs.

2. Includes conservation release from Rio Reservoir.

Diversions by New Jersey through the Delaware and Raritan Canal December 10 - 16, 2007, averaged 87.3 mgd. The average diversion for the 30-day period ending December 16, 2007 was 91.5 mgd and the maximum daily diversion was 97 mgd on December 3, 4, 2007.

OFFICE OF THE DELAWARE RIVER MASTER, MILFORD, PA.

Web address: <http://water.usgs.gov/orh/nrwww/odrm>

Summary river data for December 17 - 23, 2007 (preliminary data-subject to revision)

RESERVOIR OPERATION DATA

Millions of gallons - 24 hour period, local time

Date	Discharge to river			Diversions to New York City water supply			
	Pepacton	Cannonsville	Neversink	Pepacton	Cannonsville	Neversink	Average June 1, 2007 to date
	release begin 1200	release end 2400	release begin 1500	beginning 0800	beginning 0800	beginning 0800	
Dec. 17	55	161	48	0	0	299	630
18	55	369	59	0	235	255	629
19	55	877	42	0	204	322	629
20	55	967	42	0	201	347	629
21	55	968	42	0	201	350	628
22	55	970	42	0	201	350	628
23	58	967	42	0	0	350	626

Pepacton Reservoir (P):	Available storage Dec. 24, 2007 (0800) Spillway crest elevation 1,280.00 ft.	119.461 billion gals. 85.2 % (elev. 1,268.28 ft.) 140.190 billion gallons.
Cannonsville Reservoir (C):	Available storage Dec. 24, 2007 (0800) Spillway crest elevation 1,150.00 ft.	89.043 billion gals. 93.0 % (elev. 1,145.62 ft.) 95.706 billion gallons.
Neversink Reservoir (N):	Available storage Dec. 24, 2007 (0800) Spillway crest elevation 1,440.00 ft.	28.570 billion gals. 81.8 % (elev. 1,426.37 ft.) 34.941 billion gallons.
Combined contents, PCN:	Available storage Dec. 24, 2007 (0800) Combined capacity at spillway level.	237.074 billion gals. 87.5 % 270.837 billion gallons.
Lake Wallenpaupack:	Available storage Dec. 23, 2007 (2400) Spillway crest elevation 1,190.00 ft.	22.303 billion gals. 62.9 % (elev. 1,182.9 ft.) 35.451 billion gallons.

SEGREGATION OF FLOW, DELAWARE RIVER AT MONTAGUE AND
PRECIPITATION IN UPPER DELAWARE RIVER BASIN

Discharge in cubic feet per second, local time as routed to Montague

Date	Releases from N.Y.C. Reservoirs				Power releases		Computed uncon- trolled ²	Total Discharge	Precipitation	
	Directed release ¹	Pepacton	Cannons- ville	Never- sink	Wallen- paupack	Rio Reservoir			(inches)	
							Daily	Cumul.		
Dec. 17	0	85	249	65	500	248	5,153	6,300	.58	3.09
18	0	85	249	65	952	355	5,094	6,800	0	3.09
19	0	85	249	74	852	284	4,356	5,900	0	3.09
20	0	85	571	91	957	443	4,673	6,820	.06	3.15
21	0	85	1,357	65	817	443	4,243	7,010	0	3.15
22	0	85	1,496	65	610	319	3,765	6,340	0	3.15
23	0	85	1,497	65	340	319	3,804	6,110	.03	3.18

1. Release directed to maintain a flow at Montague of 1,750 cfs.

2. Includes conservation release from Rio Reservoir.

Diversions by New Jersey through the Delaware and Raritan Canal December 17 - 23, 2007, averaged 85.3 mgd. The average diversion for the 30-day period ending December 23, 2007 was 90.2 mgd and the maximum daily diversion was 97 mg on December 3, 4, 2007.

OFFICE OF THE DELAWARE RIVER MASTER, MILFORD, PA.

Web address: <http://water.usgs.gov/orh/nrwww/odrm>

Summary river data for December 24 - 30, 2007 (preliminary data-subject to revision)

RESERVOIR OPERATION DATA

Millions of gallons - 24 hour period, local time

Date	Discharge to river			Diversions to New York City water supply			
	Pepacton	Cannonsville	Neversink	Pepacton	Cannonsville	Neversink	Average June 1, 2007 to date
	release begin 1200	release end 2400	release begin 1500	beginning 0800	beginning 0800	beginning 0800	
Dec. 24	121	973	42	0	0	352	625
25	122	972	42	0	0	355	624
26	120	970	42	0	0	350	623
27	120	971	42	0	0	344	621
28	120	971	42	0	0	27	618
29	120	971	42	0	0	0	615
30	126	970	42	0	0	0	613

Pepacton Reservoir (P):	Available storage Dec. 31, 2007 (0800)	126.953 billion gals.	90.6 % (elev. 1,272.63 ft.)
	Spillway crest elevation 1,280.00 ft.	140.190 billion gallons.	
Cannonsville Reservoir (C):	Available storage Dec. 31, 2007 (0800)	93.333 billion gals.	97.5 % (elev. 1,148.44 ft.)
	Spillway crest elevation 1,150.00 ft.	95.706 billion gallons.	
Neversink Reservoir (N):	Available storage Dec. 31, 2007 (0800)	29.199 billion gals.	83.6 % (elev. 1,427.79 ft.)
	Spillway crest elevation 1,440.00 ft.	34.941 billion gallons.	
Combined contents, PCN:	Available storage Dec. 31, 2007 (0800)	249.485 billion gals.	92.1 %
	Combined capacity at spillway level.	270.837 billion gallons.	
Lake Wallenpaupack:	Available storage Dec. 30, 2007 (2400)	24.855 billion gals.	70.1 % (elev. 1,184.3 ft.)
	Spillway crest elevation 1,190.00 ft.	35.451 billion gallons.	

SEGREGATION OF FLOW, DELAWARE RIVER AT MONTAGUE AND
PRECIPITATION IN UPPER DELAWARE RIVER BASIN

Discharge in cubic feet per second, local time as routed to Montague

Date	Releases from N.Y.C. Reservoirs				Power releases		Computed uncon- trolled ²	Total Discharge	Precipitation	
	Directed release ¹	Pepacton	Cannons- ville	Never- sink	Wallen- paupack	Rio Reservoir			(inches)	
							Daily	Cumul.		
Dec. 24	0	85	1,501	65	298	603	16,748	19,300	.70	3.88
25	0	85	1,496	65	527	567	17,060	19,800	0	3.88
26	0	90	1,505	65	643	709	11,488	14,500	0	3.88
27	0	187	1,504	65	699	709	8,736	11,900	.01	3.89
28	0	189	1,501	65	728	851	7,566	10,900	.07	3.96
29	0	186	1,502	65	743	390	8,214	11,100	.32	4.28
30	0	186	1,502	65	858	709	10,680	14,000	0	4.28

1. Release directed to maintain a flow at Montague of 1,750 cfs.

2. Includes conservation release from Rio Reservoir.

Diversions by New Jersey through the Delaware and Raritan Canal December 24 - 30, 2007, averaged 91.9 mgd. The average diversion for the 30-day period ending December 30, 2007 was 89.9 mgd and the maximum daily diversion was 97 mg on December 3, 4, 2007.